

ISO 17458-5:2013-02 (E)

Road vehicles - FlexRay communications system - Part 5: Electrical physical layer conformance test specification

Contents		Page
Foreword		v
Introduction		vi
1	Scope	1
2	Normative references	1
3	Terms, definitions, symbols and abbreviated terms	1
3.1	Terms and definitions	1
3.2	Abbreviated terms	2
4	Document reference according to OSI model	3
5	Conventions	4
5.1	General	4
5.2	Notational conventions	4
6	Test environment	4
6.1	Test case architecture	4
6.2	Test method	5
6.3	Test environment	9
6.4	Test topology	9
6.5	Test equipment	27
7	Stress Conditions	34
7.1	Ground shift	34
7.2	Low battery voltage inside operational range	35
7.3	Undervoltage	36
7.4	Dynamic low battery voltage	37
7.5	Dynamic low supply voltage	38
7.6	Failures	41
7.7	Babbling idiot	47
7.8	Dynamic ground shift	47
7.9	EMC	48
7.10	ESD	48
7.11	Temperature tests	48
7.12	Common mode offset	48
8	Parameter List	49
8.1	General	49
8.2	Static test cases	50
8.3	Communication	50
8.4	Host Interface	54
8.5	Mode	55
8.6	Power supply	59
8.7	Environment	61
8.8	Dynamic low battery voltage	62
8.9	Dynamic low supply voltage	62
8.10	Failure	62
8.11	Functional class	65

8.12	Simulation	65
9	Test Cases for Bus Drivers	65
9.1	Configuration	66
9.2	Static test cases	89
9.3	Test cases	97
10	Test cases for Active Stars	563
10.1	General	563
10.2	Configuration	563
10.3	Static test cases	577
10.4	Test cases	584
11	Test cases for Active Stars with communication controller interface	717
11.1	Configuration	717
11.2	Static test cases	724
11.3	Test cases	728
12	Test Cases for Active Stars with host interface	795
12.1	Configuration	795
12.2	Static test cases	800
12.3	Test cases	803
	Annex A (normative) FlexRay parameters	922
	Bibliography	930