

ISO 6626-2:2013-08 (E)

Internal combustion engines - Piston rings - Part 2: Coil-spring-loaded oil control rings of narrow width made of cast iron

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Overview	1
4	Piston ring types and designation	2
4.1	DSF-C, SSF, GSF, DSF, SSF-L, DSF-NG and DSF-CNP types	2
4.2	Type DSF-C -- Coil-spring-loaded bevelled edge oil control ring, chromium-plated, and profile ground	2
4.3	Type DSF-CNP -- Coil-spring-loaded bevelled-edge oil control ring, chromium-plated not profile ground	3
4.4	Type SSF -- Coil-spring-loaded slotted oil control ring	4
4.5	Type GSF -- Coil-spring-loaded double bevelled oil control ring	5
4.6	Type DSF -- Coil-spring-loaded bevelled edge oil control ring	6
4.7	Type DSF-NG -- Coil-spring-loaded bevelled-edge oil control ring (face geometry similar to type DSF-C)	7
4.8	Type SSF-L -- Coil-spring-loaded slotted oil control ring with 0,4 mm nominal land width ..	8
5	Common features	9
5.1	Oil drainage by slots or holes	9
5.2	Plating thickness -- DSF-C and DSF-CNP (coil-spring-loaded bevelled edge oil control ring, chromium plated)	11
5.3	Peripheral edges at gap of chromium plated oil control rings	12
6	Coil springs	12
6.1	Types of coil spring	12
6.2	Coil spring excursion (extended gap)	14
6.3	Position of coil spring gap and fixing	14
6.4	Material	14
7	Tangential force and nominal contact pressure	14
7.1	Tangential force	14
7.2	Force factors	14
7.3	Tangential force, Ft	15
7.4	Classes of nominal contact pressure, po	15
8	Dimensions and tangential forces	17
Bibliography		36