

ISO 19072-2:2013-09 (E)

Road vehicles - Connection interface for pyrotechnic devices, two-way and three-way connections - Part 2: Test methods and general performance requirements

| Contents | | Page |
|---------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Functional characteristics of mated connectors | 2 |
| 4.1 | General | 2 |
| 4.2 | Visual examination | 2 |
| 4.3 | Mating and unmating | 2 |
| 4.4 | Resistance to tensile and compressive force between the connector and squib holder equipped with initiator and retainer | 3 |
| 4.5 | Mechanical strength of the retainer in the squib holder | 5 |
| 4.6 | Combination of temperature/humidity/vibration | 5 |
| 4.7 | Coding | 8 |
| 4.8 | Polarisation | 8 |
| 4.9 | Contact resistance (voltage drop), millivolt test | 8 |
| 4.10 | Insulation resistance | 10 |
| 4.11 | Withstand voltage | 10 |
| 4.12 | Thermal ageing | 10 |
| 4.13 | Opening and closing of the short-circuit | 10 |
| 4.14 | Short-circuit resistance | 11 |
| 4.15 | Rapid change of temperature (thermal shock) | 12 |
| 4.16 | Chemical fluids | 12 |
| 5 | Test sequences | 12 |
| Annex A (normative) | Sealed variant of the pyrotechnic device/initiator harness connector assembly | 14 |
| Annex B (normative) | Two-way (without ground) variant of the pyrotechnic device/initiator harness connector assembly | 16 |
| Annex C (normative) | Variant without retainer of the pyrotechnic device/initiator harness connector assembly | 18 |
| Bibliography | | 19 |