ISO/TR 10982:2013-11 (E)

Road vehicles - Test procedures for evaluating out-of-position vehicle occupant interactions with deploying air bags

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Test drive 1
4.1 General 1
4.2 50th percentile male Hybrid III dummy 2
4.3 "Small female" Hybrid III dummy 2
4.4 Three-year-old child Hybrid III dummy 2

5 Instrumentation 2
5.1 Adult size dummy 2
5.2 Three-year-old child dummy 2
5.3 Data requirements 3
5.4 Dummy test temperature 3

6 Sled pulses 3
6.1 General 3
6.2 Mild severity crash pulse 3
6.3 Moderate severity crash pulse 3

7 Static and dynamic test for driver air bag systems 6
7.1 Test set-up 6
7.2 Prepositioned driver tests 6
7.3 Acceleration-induced out-of-position driver dynamic tests 7

8 Static and dynamic tests for passenger air bag systems, using child dummy 8
8.1 General 8
8.2 Test set-up 8
8.3 Child dummy test positions 8
8.4 Child dummy static tests for passenger air bag systems 10
8.5 Child dummy dynamic tests for passenger air bag systems 10

9 Static and dynamic tests for passenger air bag systems using adult dummies 10
9.1 General 10
9.2 Test set-up 10
9.3 Adult dummy positions near instrument panel 11
9.4 Adult dummy static tests for passenger air bag systems 11
9.5 Adult dynamic tests for passenger air bag systems 11

Bibliography 13