

# ISO 8820-9:2014-05 (E)

## Road vehicles - Fuse-links - Part 9: Fuse-links with shortened tabs (Type K)

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Marking, labelling and colour coding .....</b>	<b>1</b>
<b>5</b>	<b>Tests and requirements .....</b>	<b>2</b>
<b>5.1</b>	<b>General .....</b>	<b>2</b>
<b>5.2</b>	<b>Voltage drop and connection resistance .....</b>	<b>4</b>
<b>5.3</b>	<b>Transient current cycling .....</b>	<b>6</b>
<b>5.4</b>	<b>Environmental conditions .....</b>	<b>7</b>
<b>5.5</b>	<b>Operating time-rating .....</b>	<b>7</b>
<b>5.6</b>	<b>Current steps .....</b>	<b>7</b>
<b>5.7</b>	<b>Breaking capacity .....</b>	<b>7</b>
<b>5.8</b>	<b>Strength of terminals .....</b>	<b>9</b>
<b>6</b>	<b>Dimensions .....</b>	<b>10</b>
<b>6.1</b>	<b>Basic dimensions of fuse-link .....</b>	<b>10</b>
<b>6.2</b>	<b>Designation example .....</b>	<b>11</b>
<b>7</b>	<b>Testfixture .....</b>	<b>11</b>
<b>Bibliography .....</b>		<b>13</b>