

# ISO 12617:2015-03 (E)

## Road vehicles - Liquefied natural gas (LNG) refuelling connector - 3,1 MPa connector

<b>Contents</b>		<b>Page</b>
Foreword .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>General construction requirements .....</b>	<b>3</b>
4.1	General .....	3
4.2	LNG refuelling nozzles .....	3
4.3	LNG nozzles and receptacles .....	3
4.4	Pressure rating .....	4
4.4.1	Working pressure (maximum allowable pressure) .....	4
4.4.2	Maximum service pressure .....	4
4.4.3	Hydrostatic pressure .....	4
4.4.4	Working temperature .....	4
4.5	Materials .....	4
4.5.1	Corrosion protection .....	4
4.5.2	LNG nozzle and receptacles .....	4
4.5.3	Material of the bodies of the receptacle and of the nozzle .....	4
4.6	Hand operation .....	4
4.7	Sealing exchange .....	4
4.8	Installation .....	5
<b>5</b>	<b>Nozzles .....</b>	<b>5</b>
5.1	Venting depressurization .....	5
5.2	Identification .....	5
5.3	Internal check valve .....	5
<b>6</b>	<b>Standard receptacle dimensions .....</b>	<b>5</b>
6.1	Drawing .....	5
<b>7</b>	<b>Receptacle .....</b>	<b>6</b>
7.1	Cycle life .....	6
7.2	Design .....	6
7.3	Protective cap .....	6
7.4	Mounting .....	7
7.5	Maximum working temperature .....	7
<b>8</b>	<b>Instructions .....</b>	<b>7</b>
8.1	Clarity .....	7
8.2	List of tools .....	7
<b>9</b>	<b>Marking .....</b>	<b>7</b>
9.1	Clarity .....	7
9.2	Manufacturer and International Standard information .....	7
9.3	Date of manufacture .....	8
9.3.1	First and second digits .....	8
9.3.2	Third and fourth digits .....	8
9.4	Alternative marking .....	8
9.5	Additional marking .....	8

**10 Tests 8**

<b>10.1</b>	<b>General requirements</b> .....	<b>8</b>
<b>10.2</b>	<b>User interface</b> .....	<b>9</b>
<b>10.2.1</b>	<b>Positive locking</b> .....	<b>9</b>
<b>10.2.2</b>	<b>Safe disconnection</b> .....	<b>9</b>
<b>10.2.3</b>	<b>Manual force in warm conditions</b> .....	<b>9</b>
<b>10.2.4</b>	<b>Manual force at cold conditions under frost</b> .....	<b>9</b>
<b>10.3</b>	<b>Impact resistance of a nozzle</b> .....	<b>9</b>
<b>10.4</b>	<b>Receptacle protective cap</b> .....	<b>10</b>
<b>10.5</b>	<b>Leakage at room temperature</b> .....	<b>10</b>
<b>10.5.1</b>	<b>Nozzle</b> .....	<b>10</b>
<b>10.5.2</b>	<b>Receptacle</b> .....	<b>10</b>
<b>10.6</b>	<b>Abnormal loads</b> .....	<b>11</b>
<b>10.6.1</b>	<b>General</b> .....	<b>11</b>
<b>10.6.2</b>	<b>Test in the unpressurized condition</b> .....	<b>11</b>
<b>10.6.3</b>	<b>Test in pressurized condition</b> .....	<b>11</b>
<b>10.7</b>	<b>Durability of the device (Cycle life)</b> .....	<b>12</b>
<b>10.7.1</b>	<b>Concept of the test of a device</b> .....	<b>12</b>
<b>10.7.2</b>	<b>Cycle definition</b> .....	<b>12</b>
<b>10.7.3</b>	<b>Test series</b> .....	<b>12</b>
<b>10.7.4</b>	<b>Exchange of seal of the nozzle and/or receptacle</b> .....	<b>12</b>
<b>10.8</b>	<b>Electrical conductivity</b> .....	<b>12</b>
<b>10.9</b>	<b>Hydrostatic strength</b> .....	<b>13</b>
<b>10.9.1</b>	<b>Test configurations</b> .....	<b>13</b>
<b>10.9.2</b>	<b>Test procedure and evaluation</b> .....	<b>13</b>
<b>10.10</b>	<b>Corrosion resistance</b> .....	<b>13</b>
<b>10.11</b>	<b>Non-igniting evaluation</b> .....	<b>13</b>
<b>Bibliography</b> .....		<b>14</b>