

# ISO 15118-3:2015-05 (E)

## Road vehicles - Vehicle to grid communication interface - Part 3: Physical and data link layer requirements

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Symbols and abbreviated terms .....</b>	<b>4</b>
<b>5</b>	<b>Conventions .....</b>	<b>5</b>
<b>5.1</b>	<b>Definition of OSI based services .....</b>	<b>5</b>
<b>5.2</b>	<b>Requirement structure .....</b>	<b>5</b>
<b>5.3</b>	<b>Normative references convention .....</b>	<b>5</b>
<b>6</b>	<b>System architecture .....</b>	<b>6</b>
<b>6.1</b>	<b>Communication layers overview .....</b>	<b>6</b>
<b>6.2</b>	<b>Definition of high-level communication and basic signalling .....</b>	<b>7</b>
<b>6.2.1</b>	<b>Basic signalling .....</b>	<b>7</b>
<b>6.2.2</b>	<b>High-level communication .....</b>	<b>7</b>
<b>6.3</b>	<b>Identification requirements .....</b>	<b>8</b>
<b>6.4</b>	<b>System requirements .....</b>	<b>8</b>
<b>6.4.1</b>	<b>Overview .....</b>	<b>8</b>
<b>6.4.2</b>	<b>EVSE .....</b>	<b>8</b>
<b>6.4.3</b>	<b>EV .....</b>	<b>9</b>
<b>6.5</b>	<b>Configuration of a low-layer communication module .....</b>	<b>10</b>
<b>7</b>	<b>Connection coordination .....</b>	<b>10</b>
<b>7.1</b>	<b>General .....</b>	<b>10</b>
<b>7.2</b>	<b>Overview .....</b>	<b>10</b>
<b>7.3</b>	<b>Plug-in phase .....</b>	<b>17</b>
<b>7.3.1</b>	<b>EVSE side .....</b>	<b>17</b>
<b>7.3.2</b>	<b>EV side .....</b>	<b>17</b>
<b>7.4</b>	<b>Initialization phase .....</b>	<b>17</b>
<b>7.5</b>	<b>Loss of communication .....</b>	<b>18</b>
<b>7.5.1</b>	<b>EVSE side .....</b>	<b>18</b>
<b>7.5.2</b>	<b>EV side .....</b>	<b>18</b>
<b>7.6</b>	<b>Sleep mode and wake-up .....</b>	<b>19</b>
<b>7.6.1</b>	<b>Entering the sleep mode .....</b>	<b>19</b>
<b>7.6.2</b>	<b>Wake-up .....</b>	<b>19</b>
<b>7.6.3</b>	<b>During a charge pause .....</b>	<b>20</b>
<b>7.7</b>	<b>Plug-out phase .....</b>	<b>20</b>
<b>8</b>	<b>Timings and constants .....</b>	<b>21</b>
<b>9</b>	<b>Matching EV -- EVSE process .....</b>	<b>22</b>
<b>9.1</b>	<b>Overview .....</b>	<b>22</b>
<b>9.2</b>	<b>Initialization of matching process .....</b>	<b>24</b>
<b>9.3</b>	<b>Discovery of the connected low-layer communication module .....</b>	<b>24</b>

9.4	Validation of matching decision .....	25
9.5	Set-up a logical network .....	27
9.6	Leave the logical network .....	27
9.7	Error handling .....	27
10	EMC requirements .....	27
11	Signal coupling .....	27
12	Layer 2 interfaces .....	28
12.1	Overview .....	28
12.2	Data SAP .....	28
12.3	Data link control SAP to layer 3 .....	28
Annex A (normative) HomePlug Green PHY on control pilot line .....		30
Annex B (informative) IEEE 1901.2G3-PLC profile on control pilot line .....		72
Bibliography .....		79