ISO 11452-1:2015-06 (E)

Road vehicles - Component test methods for electrical disturbances from narrowband radiated electromagnetic energy - Part 1: General principles and terminology

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 General aim and practical use 6

5 General test conditions 7
5.1 General 7
5.2 Test temperature 8
5.3 Supply voltage 8
5.3.1 Low Voltage (LV) power supply 8
5.3.2 HV d.c. power supply (excluding charger) 8
5.3.3 Charger power supply (a.c. or d.c.) for HV battery 8
5.4 Modulation 8
5.5 Dwell time 9
5.6 Frequency step sizes 9
5.7 Definition of test severity levels 10
5.8 Disturbance application 10

6 Instrumentation 10
6.1 Grounding and shielding 10
6.2 AN, AMN, and AAN 11
6.3 Power supply 11
6.3.1 LV power supply 11
6.3.2 HV d.c. power supply (excluding charger) 11
6.3.3 Charger power supply (a.c. or d.c.) 11
6.4 Load simulator 11
6.5 Test signal quality 11

7 Test procedure 12
7.1 Test plan 12
7.2 Test methods 12
7.2.1 General 12
7.2.2 Substitution method 12
7.2.3 Closed loop levelling 13
7.2.4 DUT immunity measurement 13
7.3 Test report 14

Annex A (normative)FunctionPerformanceStatusClassification(FPSC) 15

Annex B (normative)Artificialnetworks(AN),artificialmainsnetworks(AMN),and asymmetricartificialnetworks(AAN) 18

Annex C (informative)Constantpeaktestlevel 27

Annex D (informative) Example of load simulator design 30

Bibliography 33