

ISO 11452-1:2015-06 (E)

Road vehicles - Component test methods for electrical disturbances from narrowband radiated electromagnetic energy - Part 1: General principles and terminology

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	General aim and practical use	6
5	General test conditions	7
5.1	General	7
5.2	Test temperature	8
5.3	Supply voltage	8
5.3.1	Low Voltage (LV) power supply	8
5.3.2	HV d.c. power supply (excluding charger)	8
5.3.3	Charger power supply (a.c. or d.c.) for HV battery	8
5.4	Modulation	8
5.5	Dwell time	9
5.6	Frequency step sizes	9
5.7	Definition of test severity levels	10
5.8	Disturbance application	10
6	Instrumentation	10
6.1	Grounding and shielding	10
6.2	AN, AMN, and AAN	11
6.3	Power supply	11
6.3.1	LV power supply	11
6.3.2	HV d.c. power supply (excluding charger)	11
6.3.3	Charger power supply (a.c. or d.c.)	11
6.4	Load simulator	11
6.5	Test signal quality	11
7	Test procedure	12
7.1	Test plan	12
7.2	Test methods	12
7.2.1	General	12
7.2.2	Substitution method	12
7.2.3	Closed loop levelling	13
7.2.4	DUT immunity measurement	13
7.3	Test report	14
Annex A (normative)	Function Performance Status Classification (FPSC)	15
Annex B (normative)	Artificial networks (AN), artificial mains networks (AMN), and asymmetric artificial networks (AAN)	18

Annex C (informative)Constantpeaktestlevel	27
Annex D (informative) Example of load simulator design	30
Bibliography	33