ISO 21214:2015-08 (E)

Intelligent transport systems - Communications access for land mobiles (CALM) - Infra-red systems

Contents

Page

Foreword vii

Introduction viii

1 Scope 1

2 Conformance 1

3 Normative references 2

4 Termsanddefinitions 2
4.1 General terms and definitions 2
4.2 Terms and definitions of the optical parameters 4

5 Symbols (and abbreviated terms) 7

6 Requirements: Transmitter and receiver parameters 10
6.1 Transmitter wavelengths and bandwidths 10
6.2 Radiated power 11
6.2.1 Radiated power limits 11
6.2.2 Transmitter classes 11
6.3 Receiver wavelengths and bandwidths 11
6.4 Receiver class 12

7 Modulation and coding 12
7.1 Wake-up modes 12
7.1.1 85 kHz coded WU 12
7.1.2 Transmitter generic modulation parameters 13
7.1.3 Receiver generic modulation parameters 13
7.2 Communications profiles 13
7.3 Profile 0 (base profile) and profile 1 (default profile) modulation 14
7.4 Profile 2 to profile 6 14

8 Directivity and communication zones 15
8.1 Directivity parameters 15
8.2 Communication zones 16
8.2.1 Basic beam 16
8.2.2 Communication zone construction 16
8.2.3 Communication zones shortcuts 16

9 Frames and windows 17
9.1 General structure 17
9.2 Frame 18
9.2.1 Frame structure 18
9.2.2 Frame synchronisation signal (F-Sync) 19
9.3 Windows 19
9.3.1 Window structure and types 19
9.3.2 Window synchronisation (W-Sync) 19
9.3.3 Management window 20
9.3.4 Private window 22
9.3.5 Broadcast window 23

9.3.6 Multicast window 24
9.3.7 Spare window 25
9.3.8 Compatibility window 25
9.3.9 Wake-up window 25
9.4 Command alert (CA) 26
9.5 Frame and window parameters, summary 26

10 MAC commands 28
10.1 General 28
10.2 MAC commands related to the frame and window organization 29

10.2.1 Frame organization table (MC-FOT) 29
10.2.2 When generated 30
10.2.3 Effect on receipt 30
10.2.4 Frame organization table update (MC-FOTU) 30
10.2.5 Frame organization table steady (MC-FOTS) 31
10.2.6 Submaster organization table (MC-SOT) 32
10.2.7 Get submaster area (MC-GSA) 33
10.2.8 Submaster status (MC-SST) 33
10.2.9 Submaster area confirmed (MC-SAC) 34
10.2.10 Submaster area denied (MC-RESD) 34
10.2.11 Broadcast (MC-BRC) 34
10.2.12 Re-establish session (MC-REST) 35
10.2.13 Session re-establishment confirmed (MC-RESC) 36
10.2.14 Session re-establishment denied (MC-RESD) 36
10.2.15 Change master identifier (MC-CMI) 36
10.2.16 Kill all (MC-KIA) 37
10.2.17 Kill slave (MC-KIS) 37
10.2.18 De-register (MC-DREG) 38
10.2.19 Suspend all (MC-SUA) 39
10.2.20 Suspend slave (MC-SUS) 39
10.2.21 Free air time (MC-FAT) 40
10.2.22 Free air time (MC-FAT) 40
10.2.23 Spare window (MC-SPW) 41
10.2.24 Wakeup (MC-WU) 41
10.3 MAC commands related to flow control 42
10.3.1 Busy (MC-BSY) 42
10.3.2 Command not supported (MC-CNS) 42
10.3.3 Token (MC-TKN) 43
10.3.4 Block start (MC-BLS) 43
10.3.5 Control channel block start (MC-CCBS) 44
10.3.6 IEEE frame block start (MC-FBS) 44
10.3.7 Start of MAC control block (MC-SMC) 45
10.3.8 Packet start (MC-PAS) 45
10.3.9 Block start CRC16 (MC-BLS16) 46
10.3.10 Packet start CRC16 (MC-PAS16) 46
10.3.11 Packet end (MC-PAE) 47
10.3.12 Block end (MC-BLE) 47
10.3.13 Transmission acknowledged (MC-TAck) 48
10.3.14 Transmission acknowledged and (MC-TAck&) 48
10.3.15 Transmission NOT acknowledged (MC-TNAck) 49
10.3.16 Transmission NOT acknowledged and (MC-TNAck&) 49
10.3.17 Retransmission request (MC-RTQ) 49
10.3.18 Block acknowledge (MC-BAck) 50
10.4 MAC commands related to the registration process 50
10.4.1 Registration enable (MC-REN) 50
10.4.2 Registration request (MC-RRQ) 51
10.4.3 Identifier request (MC-IDQ) 52
10.4.4 Identifier response (MC-IDP) 52
10.4.5 Registration confirmation (MC-REC) 53
10.5 MAC commands related to the PHY layer parameters 53
10.5.1 Profiles request (MC-PRQ) 53

10.5.2 Profiles response (MC-PRP) 54
10.5.3 Request new profile (MC-RNP) 55
10.5.4 Set profile (MC-SPR) 55
10.5.5 Set profile confirmation (MC-SPC) 56
10.5.6 Set multicast profile (MC-SMP) 56
10.6 MAC commands related to test and services 57
10.6.1 Ping (MC-PING) 57
10.6.2 Pong (MC-PONG) 57
10.6.3 Status request1 (MC-SRQ1) 57
10.6.4 Status request2 (MC-SRQ2) 58
10.6.5 Status request3 (MC-SRQ3) 59
10.6.6 Status request4 (MC-SRQ4) 60
10.6.7 Status response1 (MC-SR1) 61
10.6.8 Status response2 (MC-SR2) 62
10.6.9 Status response3 (MC-SR3) 62
10.6.10 Status response4 (MC-SR4) 63
10.6.11 Echo alert (MC-EA) 64
10.6.12 Echo request (MC-ERQ) 65
10.6.13 Echo (MC-ECH) 65
10.6.14 Service table (MC-ST) 66
10.6.15 Service table request (MC-STQ) 67
10.6.16 Service subscribe (MC-SVS) 67
10.6.17 Service (MC-SVC) 68
10.6.18 Service unsubscribe (MC-SVU) 68
10.7 MAC command set overview 69

11 Registration procedure 71
11.1 General 71
11.2 Normal registration procedure 72
11.2.1 Temporary identifier 72
11.2.2 TempID codes 72
11.3 Sequence of the registration procedure without collision 72
11.4 Sequence of the registration procedure with collision 73
11.4.1 Both signals appear with equal signal strength 73
11.4.2 Both signals appear with different signal strength 74
11.4.3 Identical TempIDs 74
11.5 Handover and re-registration 75
11.5.1 Cancel TempID 75
11.5.2 Advise adjacent masters 75
11.6 Registration process timers 75

12 Window management 75
12.1 General 75
12.2 Window allocation by frame organization tables 76
12.3 Spare windows 76
12.4 Windows for isochronous services 76

13 IR Management entity 77
13.1 General 77
13.2 MAC command not supported 77
13.3 Communication profiles 77
13.4 Equipment status 77
13.5 Testing 77
13.6 Registration 77
13.7 Session management 78
13.8 Communication 79
13.8.1 Organization of IR communication 79
13.8.2 Unique block number reference 79
13.9 Window management 80
13.10 MAC Tunnel 80

14 Adaptation 80

14.1 Architecture 80
14.2 IR-CAL 81
14.2.1 Communication SAP 81
14.2.2 Communication types 81
14.2.3 WLAN functionality 82
14.2.4 MAC addresses 84
14.2.5 Fragmentation and defragmentation 85
14.3 IR-MAE 85

15 Adoption of other standards and internationally accepted practices 86

16 Marking and labelling 86

17 Declaration of patents and Intellectual Property 86

Annex A (normative)Codinganderrorcorrectionofprofiles0and1andofcommands 89

Annex B (normative)Codingandmodulationofprofile2toprofile6 91

Annex C (informative) Link power budget 98

Annex D (informative) Link directivity considerations 103

Annex E (informative) Compatibility of CALM and non-CALM infrared systems 105

Annex F (normative)SpecificationofMR-IRcommunicationprotocolforcompatibilitywith previously published version 133

Bibliography 135