

DIN EN 16454:2015-12 (E)

Intelligent transport systems - ESafety - ECall end to end conformance testing

Contents		Page
European foreword		9
Introduction		10
1	Scope	11
2	Normative references	11
3	Terms and definitions	12
4	Symbols and abbreviations	17
5	Conformance	19
5.1	General	19
5.2	General conditions	19
6	General overview of the eCall transaction for pan-European eCall	20
7	How to use this Standard	24
7.1	Layout and procedures	24
7.2	System under test	25
7.3	Accelerated test procedures	26
7.4	Accelerated test procedures for IVSs	26
7.4.1	Accelerated test procedures for all types of PE eCall IVS	26
7.4.2	Additional accelerated test procedures for PE eCall only IVS	28
7.5	Accelerated test procedures for MNOs	28
7.6	Accelerated test procedures for PSAPs - PE eCall	29
7.7	Accelerated test procedures for PSAPs - TPS-eCall	30
7.8	Accelerated test procedures for TPSPs	30
8	Requirements	31
8.1	Requirements - General objectives	31
8.1.1	State transitions	31
8.1.2	Classification of testing	41
8.1.3	CTP naming conventions	43
8.1.4	CTP naming convention for IVS conformance tests	44
8.2	CTP structure	44
9	Conformance test requirements for in-vehicle user equipment and systems (IVS)	46
9.1	Conformance test requirements for in-vehicle user equipment and systems for Pan European eCall	46
9.2	Test objectives and purposes	46
9.3	Classification of testing and referenced tests for in-vehicle user equipment for Pan European eCall IVS	46
9.3.1	Taxonomy of testing	46
9.3.2	Referenced tests	46
9.4	State transition conformance tests for in-vehicle equipment and system to comply to Standards for pan European eCall	47
9.4.1	Conformance requirement	47
9.4.2	Use case test objectives by stage	47
9.4.3	CTP 1.1.0.1 Conformance to ETSI TS 102 936-1 and ETSI TS 102 936-2 - PE eCall IVS	50
9.4.4	CTP 1.1.0.2 Test for conformance to valid SIM/USIM - PE eCall	51

9.4.5	CTP 1.1.0.3 Automatic eCall triggering does not occur when ignition OFF - PE eCall IVS	52
9.4.6	CTP 1.1.1.1 Power on and self test - PE eCall IVS	53
9.4.7	CTP 1.1.2.1 eCall automatically activated - PE eCall IVS	54
9.4.8	CTP 1.1.2.2 Automatically triggered eCall in progress was not disconnected upon a new eCall trigger - PE eCall IVS	55
9.4.9	CTP 1.1.2.3 Post-side-crash performance of automatic trigger - IVS	56
9.4.10	CTP 1.1.2.4 Post-frontal-crash performance of automatic trigger - IVS	57
9.4.11	CTP 1.1.2.5 Performance of automatic trigger - different crash types - IVS	58
9.4.12	CTP 1.1.3.1 eCall manually activated - PE eCall IVS	59
9.4.13	CTP 1.1.3.2 Manually triggered eCall in progress was not disconnected upon a new eCall trigger - PE eCall IVS	60
9.4.14	CTP 1.1.4.1 Test eCall activated - PE eCall IVS	61
9.4.15	CTP 1.1.5.1 Network registration - PE eCall IVS	62
9.4.16	CTP 1.1.5.2 Manual termination of eCall by vehicle occupants not allowed (automatically triggered eCall) - PE eCall IVS	63
9.4.17	CTP 1.1.5.3 Manual termination of eCall by vehicle occupants not allowed (manually triggered eCall) - PE eCall IVS	64
9.4.18	CTP 1.1.5.4 Automatically triggered eCall in progress was not disconnected when ignition is switched to OFF - PE eCall IVS	65
9.4.19	CTP 1.1.5.5 Manually triggered eCall in progress was not disconnected when ignition is switched to OFF - PE eCall IVS	66
9.4.20	CTP 1.1.5.6 Priority over conflicting communication - PE eCall IVS	67
9.4.21	CTP 1.1.5.7 Network registration is re-tried when network registration attempt was not successful - PE eCall IVS	68
9.4.22	CTP 1.1.6.1 Mute IVS and vehicle audio - PE eCall IVS	68
9.4.23	CTP 1.1.7.1 Set-up TS12 call with eCall identifier (flag) set to `automatic' - PE eCall IVS	69
9.4.24	CTP 1.1.8.1 Set-up TS12 call with eCall identifier (flag) set to `manual' - PE eCall IVS	70
9.4.25	CTP 1.1.9.1 Set-up TS11 call to test number - PE eCall IVS	71
9.4.26	CTP 1.1.10.1 eCall is attempted when no networks are available (limited service condition) - PE eCall IVS	72
9.4.27	CTP 1.1.10.2 Re-dial attempt completed within 2 minutes after eCall is dropped - PE eCall IVS	73
9.4.28	CTP 1.1.10.3 Duration of eCall Initiation signal - PE eCall IVS	74
9.4.29	CTP 1.1.11.1 Send MSD with indicator set to `Automatically Initiated eCall' (AleC) - PE eCall IVS	75
9.4.30	CTP 1.1.12.1 Send MSD with indicator set to `Manually Initiated eCall' (MleC) - PE eCall IVS	76
9.4.31	CTP 1.1.13.1 Send MSD with indicator set to `Test Call' - PE eCall IVS	77
9.4.32	CTP 1.1.14.1 Verify MSD transfer - PE eCall IVS	78
9.4.33	CTP 1.1.14.2 Un-mute IVS audio when AL-ACK received - PE eCall IVS	79
9.4.34	CTP 1.1.15.1 Establish voice link to PSAP - PE eCall IVS	80
9.4.35	CTP 1.1.15.2 MSD transfer request while eCall conversation in progress - PE eCall IVS	81
9.4.36	CTP 1.1.15.3 eCall continuation when SEND MSD request not received (T5 expired) - PE eCall IVS	83
9.4.37	CTP 1.1.15.4 Call continuation when AL-ACK not received (T6 expired) - PE eCall IVS	84
9.4.38	CTP 1.1.15.5 MSD is transferred continuously until T7 expires and IVS reconnects loudspeaker and microphone on its expiry - PE eCall IVS	85
9.4.39	CTP 1.1.16.1 Clear down call automatically - PE eCall IVS	86
9.4.40	CTP 1.1.16.2 IVS clears down the eCall upon T2 expiry - PE eCall IVS	88
9.4.41	CTP 1.1.16.3 IVS registers recent eCalls - PE eCall IVS	89
9.4.42	CTP 1.1.17.1 Call-back allowed and able to be answered by IVS - PE eCall IVS	90
9.4.43	CTP 1.1.17.2 Call-back answered by IVS in the event of abnormal termination - PE eCall IVS	91
9.4.44	CTP 1.1.17.3 MSD transfer occurs upon PSAP request during call-back - PE eCall IVS	92
9.4.45	CTP 1.1.17.4 Remain registered for 1 hr - PE eCall IVS	93
9.5	State transition test scripts for in-vehicle equipment and system to comply to Standards for pan European eCall - additional tests for eCall only systems	94
9.5.1	General	94
9.5.2	CTP 1.1.1.2 IVS does not perform registration after power-up - PE eCall only IVS	95
9.5.3	CTP 1.1.1.3 IVS periodically scans and maintains a list of available PLMNs - PE eCall only	95

9.5.4	CTP1.1.10.4 Verify that PLMN registration procedure is executed upon initiating an eCall - PE eCall only IVS	96
9.5.5	CTP 1.1.17.5 Remain registered for 1 hr 12 hr - PE eCall only IVS	97
9.6	State transition conformance test requirements for in-vehicle user equipment for eCall TPS-IVS via a third party service provider	98
9.6.1	General	98
9.6.2	Test objectives and purposes	98
9.6.3	Taxonomy of testing and referenced tests	98
9.6.4	Taxonomy of testing	98
9.7	Use case conformance tests for in-vehicle equipment and system to comply to Standards for third party service provider eCall	98
9.7.1	Conformance requirement	98
9.7.2	Use case test objectives by stage	99
9.8	State transition test scripts for TPS in-vehicle equipment and system to comply to Standards for third party services supported eCall	101
9.8.1	General	101
9.8.2	CTP 1.2.0 Pre operation - TPS-IVS	102
9.8.3	CTP 1.2.1 Power on self test - TPS-IVS	104
9.8.4	CTP 1.2.2 Automatically activate eCall - TPS-IVS	105
9.8.5	CTP 1.2.3 Manually activate eCall - TPS-IVS	113
9.8.6	CTP 1.2.4 Stop conflicting communication - TPS-IVS	117
9.8.7	CTP 1.2.5 Establish voice link to TPSP - TPS-IVS	118
9.8.8	CTP 1.2.6 Send IVS dataset to TPSP - TPS-IVS	123
9.8.9	CTP 1.2.7 Establish voice link between PSAP and occupants - TPS-IVS	129
9.8.10	CTP 1.2.8 Cleardown call - TPS-IVS	130
9.8.11	CTP 1.2.9 Allow call-cack into vehicle - TPS-IVS	131
10	Conformance tests for mobile network operators	136
10.1	Test objectives and purposes	136
10.1.1	General	136
10.1.2	Default assumptions	136
10.2	Taxonomy of testing and referenced tests	136
10.3	Use case conformance tests for mobile network operator systems to comply to Standards for pan European eCall	136
10.3.1	Conformance requirement	136
10.3.2	Use case test objectives by stage	136
10.4	State transition test scripts for mobile network operators to demonstrate compliance with Pan European eCall Standards	138
10.4.1	General	138
10.4.2	CTP 2.0.1 Keep SIMs/USIMs alive even though not in regular operation - MNO	139
10.4.3	CTP 2.0.2 MNO supports general eCall relevant requirements	140
10.4.4	CTP 2.0.3 Decommission SIM/USIM - MNO	141
10.4.5	CTP 2.0.4 Support eCall Flag - MNO	142
10.4.6	CTP 2.1.1 Accept registration - Home network - MNO	142
10.4.7	CTP 2.1.2 Accept registration - Roaming -MNO	143
10.4.8	CTP 2.2.1.1 Receive TS12 voice call (automatically initiated) - MNO	144
10.4.9	CTP 2.2.1.2 Route call to 'most appropriate' PSAP - MNO	145
10.4.10	CTP 2.2.1.3 Provide TS12 data/caller ID - MNO	146
10.4.11	CTP 2.2.2.1 Receive TS12 voice call (manual initiated) - MNO	147
10.4.12	CTP 2.2.3.1 Test for receiving test eCall (TS11)	147
10.4.13	CTP 2.2.3.2 Route call to non-emergency number - MNO	147
10.4.14	CTP 2.2.3.3 Provide TS11 data - MNO	148
10.4.15	CTP 2.3.1 Call in progress-MNO	148
10.4.16	CTP 2.4.1 Call cleardown - MNO	149
10.4.17	CTP 2.5.1 Support call-back - MNO	150
10.4.18	CTP 2.6.1 Maintain registration for 1-12 hours - MNO	150
10.4.19	CTP 2.7.1 Maintain call records - MNO	150
10.5	Use case conformance tests for mobile network operator systems to comply to Standards for TPS-eCall	151
10.5.1	Conformance requirement	151
10.5.2	Use case test objectives by stage	151

10.6	State transition test scripts for mobile network operators to demonstrate compliance with TPS-eCall Standards	151
10.6.1	CTP 2.11.1 MNO supports general TPS-eCall relevant requirements	151
10.6.2	CTP 2.11.2 Support call-back - MNO	151
11	Conformance tests for PSAP systems	152
11.1	Test objectives and purposes	152
11.2	Taxonomy of testing and referenced tests	152
11.2.1	Taxonomy of testing	152
11.2.2	Referenced tests	152
11.3	Use case conformance tests for PSAP systems to comply to Standards for pan European eCall	152
11.3.1	Conformance requirement	152
11.3.2	Use case test objectives by stage	152
11.4	State transition conformance tests for PSAPs - PE eCall	153
11.4.1	General	153
11.4.2	CTP 3.1.0.1 Provide MNOs with appropriate routing data - Member State/ PSAP PE eCall	155
11.4.3	CTP 3.1.0.2 Maintain map geo-information - PSAP PE eCall	156
11.4.4	CTP 3.1.1.1 Receive automatically initiated eCall - PSAP PE eCall	157
11.4.5	CTP 3.1.1.2 Receive manually initiated eCall - PSAP PE eCall	158
11.4.6	CTP 3.1.2 Receive TS12 data- Caller ID & location - PSAP PE eCall	159
11.4.7	CTP 3.1.3.1 Recognise eCall and route to in-band modem - PSAP PE eCall	160
11.4.8	CTP 3.1.3.2 PSAP equipment failure - PSAP PE eCall	161
11.4.9	CTP 3.1.3.3 PSAP modem failure before link layer ACK is sent - PSAP PE eCall	162
11.4.10	CTP 3.1.4 eCall received at in-band modem - PSAP PE eCall	163
11.4.11	CTP 3.1.5.1 Validate initiation signal - PSAP PE eCall	164
11.4.12	CTP 3.1.5.2 Route to operator after T4 expiration - PSAP PE eCall	165
11.4.13	CTP 3.1.6 Request MSD - PSAP PE eCall	166
11.4.14	CTP 3.1.7.1 Receive MSD - PSAP PE eCall	167
11.4.15	CTP 3.1.7.2 Verify status bit in AL-ACK upon positive ACK- PSAP PE eCall	168
11.4.16	CTP 3.1.7.3 Verify MSD transfer upon T8 expiration - PSAP PE eCall	169
11.4.17	CTP 3.1.7.4 Verify transfer of corrupted MSD - PSAP PE eCall	170
11.4.18	CTP 3.1.7.5 Verify PSAP behaviour when MSD format check fails- PSAP PE eCall	171
11.4.19	CTP 3.1.8 ACK - PSAP PE eCall	171
11.4.20	CTP 3.1.9 Route voice and MSD to operator - PSAP PE eCall	172
11.4.21	CTP 3.1.10 Display TS12 data and MSD to operator - PSAP PE eCall	173
11.4.22	CTP 3.1.11 Decode VIN - PSAP PE eCall	174
11.4.23	CTP 3.1.12 Talk to vehicle occupants - PSAP PE eCall	175
11.4.24	CTP 3.1.13 Request new MSD before call clear-down - PSAP PE eCall	176
11.4.25	CTP 3.1.14.1 Call clear-down - PSAP PE eCall	177
11.4.26	CTP 3.1.14.2 Verify status bit in AL-ACK upon clear-down - PSAP -PE eCall	178
11.4.27	CTP 3.1.15 Call-back to vehicle - PSAP PE eCall	179
11.4.28	CTP 3.1.16 Request new MSD after call clear-down - PSAP PE eCall	180
11.5	State transition conformance tests for PSAPs - TPS-eCall	181
11.5.1	General	181
11.5.2	CTP 3.2.0.1 TPSP - PSAP agreement - PSAP TPS eCall	182
11.5.3	CTP 3.2.0.2 Provide areas of responsibility and contact numbers to approved TPSPs -PSAP TPS-eCall	183
11.5.4	CTP 3.2.0.3 Agreement on necessary language support - PSAP TPS eCall	185
11.5.5	CTP 3.2.0.4 Agree electronic data connection and provide details to approved TPSPs - PSAP TPS eCall	186
11.5.6	186 11.5.7 CTP 3.2.0.5 Provide PSAP data addresses and security access to approved TPSPs - PSAP TPS eCall	188
11.5.8	CTP 3.2.1 Receive eCall notification from TPSP (not TS12) -PSAP TPS eCall	189
11.5.9	CTP 3.2.2 Route call to operator - PSAP TPS eCall	190
11.5.10	CTP 3.2.3 Connection, TSD transmission, display relevant information to PSAP operator -PSAP TPS-eCall	191
11.5.11	CTP 3.2.4 PSAP Operator: Talk with TPSP operator and receive relevant information - PSAP TPS eCall	193
11.5.12	CTP 3.2.5 Talk to vehicle occupants - PSAP TPS-eCall	194
11.5.13	CTP 3.2.6 Request new TSD before call clear-down -PSAP TPS-eCall	195
11.5.14	CTP 3.2.7 Inform TPSP that call can be ended - PSAP TPS eCall	196

11.5.15	CTP 3.2.8 Call cleardown with TPSP -PSAP TPS-eCall	197
11.5.16	CTP 3.2.9 Call-back to TPSP - PSAP TPS-eCall	198
11.5.17	CTP 3.2.10 Call-back to vehicle - PSAP TPS eCall	199
11.5.18	CTP 3.2.11 Call cleardown with vehicle - PSAP TPS eCall	200
12	State transition conformance tests for TPS-eCall	201
12.1	Related specifications and conformance requirements	201
12.2	TPSP general tests (applicable to both TPS-eCall responder and TPS-eCall notifier)	201
12.2.1	General	201
12.2.2	CTP 4.0.1 Agree service level agreement and/or Standard ways of working with PSAPs - TPSP	203
12.2.3	CTP 4.0.2 Receive PSAP areas of responsibility and contact numbers - TPSP	204
12.2.4	CTP 4.0.3 Agree necessary language support - TPSP	205
12.2.5	CTP 4.0.4 Agree electronic data connection details with PSAPs - TPSP	207
12.2.6	CTP 4.0.5 Evidence quality procedures - TPSP	208
12.2.7	CTP 4.0.6 Verify automatic call distribution (ACD) system - TPSP	210
12.2.8	CTP 4.0.7 Check link from MNO - TPSP	211
12.2.9	CTP 4.0.8 Deal with transmission failures - TPSP	211
12.2.10	CTP 4.0.9 Update GIS - TPSP	212
12.2.11	CTP 4.0.10 Protection of privacy - TPSP	213
12.3	TPS-eCall responder tests - TPS-R	214
12.3.1	General	214
12.3.2	CTP 4.1.1 Receive TPS-eCall from vehicle - TPS-R	215
12.3.3	CTP 4.1.2 Process incoming call - TPS-R	218
12.3.4	CTP 4.1.3 Talk with vehicle occupants and receive relevant information - TPS-R	220
12.3.5	CTP 4.1.4 Trigger PSAP notification - TPS-R	223
12.3.6	CTP 4.1.5 Make voice connection between vehicle and PSAP if required - TPS-R	223
12.3.7	CTP 4.1.6 Confirmation received from PSAP that call with vehicle can be ended - TPS-R	224
12.3.8	CTP 4.1.7 Call cleardown with vehicle - TPS-R	225
12.3.9	CTP 4.1.8 Call-back to vehicle - TPS-R	226
12.4	TPS-eCall notifier tests - TPS-N	227
12.4.1	General	227
12.4.2	CTP 4.2.1 Emergency situation likely to require assistance - TPS-N	228
12.4.3	CTP 4.2.2 Establish contact with PSAP - TPS-N	228
12.4.4	CTP 4.2.3 Talk with PSAP operator and notify relevant information - TPS-N	233
12.4.5	CTP 4.2.4 Establish voice link between PSAP and vehicle occupants if required by PSAP - TPS-N	235
12.4.6	CTP 4.2.5 Respond to electronic data update request - TPS-N	237
12.4.7	CTP 4.2.6 PSAP informs that call can be ended - TPS-N	237
12.4.8	CTP 4.2.7 Call cleardown to PSAP - TPS-N	237
12.4.9	CTP 4.2.9 Call-back from PSAP - TPS-N	238
13	Marking, labelling and packaging	238
14	Declaration of patents and intellectual property	238
Annex A (normative) Proforma conformance test report for Pan European eCall in-vehicle system (IVS)		239
A.1	A.1 Conformance test report	239
A.2	A.1.1 System under test:	239
A.2.1	A.1.2 System under test identification	239
A.2.2	A.1.3 Testing environment	240
A.2.3	A.1.4 Limits and reservation	240
A.2.4	A.1.5 Comments	240
A.3	A.2 SUT conformance status	241
A.4	A.3 Static conformance summary	241
A.5	A.4 Dynamic conformance summary	241
A.6	A.5 Static conformance review report	242
A.7	A.6 Test campaign report	243
A.7.1	A.7 Observations	244

Annex B (normative) ProForma conformance test report for Third Party Service Provider In-Vehicle System (TPS-IVS)	245
B.1	B.1 Conformance test report 245
B.2	B.1.1 System under test: 245
B.2.1	B.1.2 System under test identification 245
B.2.2	B.1.3 Testing environment 246
B.2.3	B.1.4 Limits and reservation 246
B.2.4	B.1.5 Comments 246
B.3	B.2 SUT conformance status 247
B.4	B.3 Static conformance summary 247
B.5	B.4 Dynamic conformance summary 247
B.6	B.5 Static conformance review report 248
B.7	B.6 Test campaign report 249
B.7.1	B.7 Observations 249
Annex C (normative) ProForma conformance test report for mobile network operator (MNO)	250
C.1	C.1 Conformance test report 250
C.2	C.1.1 System under test: 250
C.2.1	C.1.2 System under test identification 250
C.2.2	C.1.3 Testing environment 251
C.2.3	C.1.4 Limits and reservation 251
C.2.4	C.1.5 Comments 251
C.3	C.2 SUT conformance status 252
C.4	C.3 Static conformance summary 252
C.5	C.4 Dynamic conformance summary 252
C.6	C.5 Static conformance review report 253
C.7	C.6 Test campaign report 254
C.7.1	C.7 Observations 254
Annex D (normative) ProForma conformance test report for public service answering point (PSAP)	255
D.1	D.1 Conformance test report 255
D.2	D.1.1 System under test: 255
D.2.1	D.1.2 System under test identification 255
D.2.2	D.1.3 Testing environment 256
D.2.3	D.1.4 Limits and reservation 256
D.2.4	D.1.5 Comments 256
D.3	D.2 SUT conformance status 257
D.4	D.3 Static conformance summary 257
D.5	D.4 Dynamic conformance summary 257
D.6	D.5 Static conformance review report 258
D.7	D.6 Test campaign report 259
D.7.1	D.7 Observations 260
Annex E (normative) ProForma conformance test report for third party service provider (TPS-eCall)	261
E.1	E.1 Conformance test report 261
E.2	E.1.1 System under test: 261
E.2.1	E.1.2 System under test identification 261
E.2.2	E.1.3 Testing environment 262
E.2.3	E.1.4 Limits and reservation 262
E.2.4	E.1.5 Comments 262
E.3	E.2 SUT conformance status 263
E.4	E.3 Static conformance summary 263
E.5	E.4 Dynamic conformance summary 263
E.6	E.5 Static conformance review report 264
E.7	E.6 Test campaign report 265
E.7.1	E.7 Observations 265
Bibliography	267