

ISO 11898-1:2015-12 (E)

Road vehicles - Controller area network (CAN) - Part 1: Data link layer and physical signalling

Contents		Page
Foreword		vi
Introduction		vii
1	Scope	1
2	Conformance	1
3	Normative references	2
4	Terms and definitions	2
5	Symbols and abbreviated terms	5
6	Basic concepts of CAN	7
6.1	CAN properties	7
6.2	Frames	8
6.3	Bus access method	8
6.4	Information routing	8
6.5	Network flexibility	8
6.6	Data consistency	8
6.7	Remote data request	8
6.8	Error detection	9
6.9	Error signalling and recovery time	9
6.10	ACK	9
6.11	Automatic retransmission	9
6.12	Fault confinement	9
6.13	Error-active	9
6.14	Error-passive	9
6.15	Bus-off	10
7	Layered architecture of CAN	10
7.1	Reference to OSI model	10
7.2	Protocol specification	11
7.3	Format description of services	11
7.3.1	Format description of service primitives	11
7.3.2	Types of service primitives	12
7.4	LLC interface	12
8	Description of LLC sub-layer	12
8.1	General	12
8.2	Services of LLC sub-layer	13
8.2.1	Types of connectionless-mode transmission services	13
8.2.2	Service primitive specification	13
8.3	Functions of LLC sub-layer	18
8.3.1	General	18
8.3.2	Frame acceptance filtering	18
8.3.3	Overload notification	18
8.3.4	Recovery management	19
8.4	Structure of LLC frames	19
8.4.1	General	19

8.4.2	Specification of LLC DF	19
8.4.3	Specification of LLC RF	20
8.5	Limited LLC frames	21
9	Interface between LLC and MAC	21
9.1	Services	21
9.2	Time and time triggering	21
9.2.1	Description	21
9.2.2	Time base	21
9.2.3	Time reference point	21
9.2.4	Event generation	22
9.3	Disabling automatic retransmission	22
9.3.1	Retransmission of frames	22
9.4	Message time stamping	22
10	Description of MAC sub-layer	22
10.1	General	22
10.2	Services of MAC sub-layer	22
10.2.1	Service description	22
10.2.2	Service primitives specification	23
10.3	Functional model of MAC sub-layer architecture	27
10.3.1	Capability	27
10.3.2	Frame transmission	27
10.3.3	Frame reception	28
10.4	Structure of MAC frames	29
10.4.1	Description	29
10.4.2	Specification of MAC DF	29
10.4.3	Specification of MAC RF	34
10.4.4	Specification of EF	34
10.4.5	Specification of OF	35
10.4.6	Specification of inter-frame space	36
10.5	Frame coding	37
10.6	Frame acknowledgement	37
10.7	Frame validation	37
10.8	Order of bit transmission	38
10.9	Medium access method	39
10.9.1	General	39
10.9.2	Multi-master	39
10.9.3	Bus access	40
10.9.4	Bus integration state	40
10.9.5	Protocol exception event	40
10.9.6	Transmission of MAC frames	40
10.9.7	Content-based arbitration	40
10.9.8	Frame priority	41
10.9.9	Collision resolution	41
10.9.10	Disabling of frame formats	41
10.10	MAC data consistency	41
10.11	Error detection	41
10.12	Error signalling	42
10.13	Overload signalling	43
10.14	Bus monitoring	44
10.15	Restricted operation	44
11	PLspecification	44
11.1	General and functional modelling	44
11.2	Services of PL	44
11.2.1	Description	44
11.2.2	PCS_Data.Request	45
11.2.3	PCS_Data.Indicate	45
11.2.4	PCS_Status.Transmitter	45
11.2.5	PCS_Status.Receiver	45

11.3	PCS specification	45
11.3.1	Bit encoding/decoding	45
11.3.2	Synchronization	50
11.3.3	Transmitter delay compensation	52
11.4	AUI specification	54
11.4.1	General	54
11.4.2	PCS to PMA messages	55
11.4.3	PMA to PCS message	55
12	Description of supervisor FCE	55
12.1	Fault confinement	55
12.1.1	Objectives	55
12.1.2	Strategies	55
12.1.3	Fault confinement interface specification	56
12.1.4	Rules of fault confinement	58
12.1.5	Network start-up	60
12.2	Bus failure management	60
Annex A (informative) Additional Information		61
Bibliography		65