

DIN EN ISO 15118-3:2016-08 (E)

Road vehicles - Vehicle to grid Communication interface - Part 3: Physical and data link layer requirements (ISO 15118-3:2015); English version EN ISO 15118-3:2016

Contents		Page
Foreword		v
Introduction		vi
1 Scope		1
2 Normative references		1
3 Terms and definitions		1
4 Symbols and abbreviated terms		4
5 Conventions		5
5.1 Definition of OSI based services		5
5.2 Requirement structure		5
5.3 Normative references convention		5
6 System architecture		6
6.1 Communication layers overview		6
6.2 Definition of high-level communication and basic signalling		7
6.2.1 Basic signalling		7
6.2.2 High-level communication		7
6.3 Identification requirements		8
6.4 System requirements		8
6.4.1 Overview		8
6.4.2 EVSE		8
6.4.3 EV		9
6.5 Configuration of a low-layer communication module		10
7 Connection coordination		10
7.1 General		10
7.2 Overview		10
7.3 Plug-in phase		17
7.3.1 EVSE side		17
7.3.2 EV side		17
7.4 Initialization phase		17
7.5 Loss of communication		18
7.5.1 EVSE side		18
7.5.2 EV side		18
7.6 Sleep mode and wake-up		19
7.6.1 Entering the sleep mode		19
7.6.2 Wake-up		19
7.6.3 During a charge pause		20
7.7 Plug-out phase		20
8 Timings and constants		21
9 Matching EV — EVSE process		22
9.1 Overview		22
9.2 Initialization of matching process		24
9.3 Discovery of the connected low-layer communication module		24
9.4 Validation of matching decision		25
9.5 Set-up a logical network		27
9.6 Leave the logical network		27
9.7 Error handling		27

10 EMC requirements27

11 Signal coupling27

12 Layer 2 interfaces28

 12.1 Overview28

 12.2 Data SAP28

 12.3 Data link control SAP to layer 328

Annex A (normative) HomePlug Green PHY on control pilot line30

Annex B (informative) IEEE 1901.2 G3-PLC profile on control pilot line72

Bibliography79