DIN EN ISO 15118-3:2016-08 (E)

Road vehicles - Vehicle to grid Communication interface - Part 3: Physical and data link layer requirements (ISO 15118-3:2015); English version EN ISO 15118-3:2016

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Symbols and abbreviated terms **4**

5 Conventions **5**
5.1 Definition of OSI based services 5
5.2 Requirement structure 5
5.3 Normative references convention 5

6 System architecture **6**
6.1 Communication layers overview 6
6.2 Definition of high-level communication and basic signalling 7
6.2.1 Basic signalling 7
6.2.2 High-level communication 7
6.3 Identification requirements 8
6.4 System requirements 8
6.4.1 Overview 8
6.4.2 EVSE 8
6.4.3 EV 9
6.5 Configuration of a low-layer communication module 10

7 Connection coordination **10**
7.1 General 10
7.2 Overview 10
7.3 Plug-in phase 17
7.3.1 EVSE side 17
7.3.2 EV side 17
7.4 Initialization phase 17
7.5 Loss of communication 18
7.5.1 EVSE side 18
7.5.2 EV side 18
7.6 Sleep mode and wake-up 19
7.6.1 Entering the sleep mode 19
7.6.2 Wake-up 19
7.6.3 During a charge pause 20
7.7 Plug-out phase 20

8 Timings and constants **21**

9 Matching EV — EVSE process **22**
9.1 Overview 22
9.2 Initialization of matching process 24
9.3 Discovery of the connected low-layer communication module 24
9.4 Validation of matching decision 25
9.5 Set-up a logical network 27
9.6 Leave the logical network 27
9.7 Error handling 27

10 EMC requirements **27**

11 Signal coupling **27**

12 Layer 2 interfaces **28**

12.1 Overview 28

12.2 Data SAP 28

12.3 Data link control SAP to layer 3 28

Annex A (normative) **HomePlug Green PHY on control pilot line** **30**

Annex B (informative) **IEEE 1901.2 G3-PLC profile on control pilot line** **72**

Bibliography **79**