

DIN EN ISO 15118-3:2016-08 (E)

Road vehicles - Vehicle to grid Communication interface - Part 3: Physical and data link layer requirements (ISO 15118-3:2015); English version EN ISO 15118-3:2016

Contents

Page

Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	4
5 Conventions	5
5.1 Definition of OSI based services.....	5
5.2 Requirement structure.....	5
5.3 Normative references convention.....	5
6 System architecture	6
6.1 Communication layers overview.....	6
6.2 Definition of high-level communication and basic signalling.....	7
6.2.1 Basic signalling.....	7
6.2.2 High-level communication.....	7
6.3 Identification requirements.....	8
6.4 System requirements.....	8
6.4.1 Overview.....	8
6.4.2 EVSE.....	8
6.4.3 EV.....	9
6.5 Configuration of a low-layer communication module.....	10
7 Connection coordination	10
7.1 General.....	10
7.2 Overview.....	10
7.3 Plug-in phase.....	17
7.3.1 EVSE side.....	17
7.3.2 EV side.....	17
7.4 Initialization phase.....	17
7.5 Loss of communication.....	18
7.5.1 EVSE side.....	18
7.5.2 EV side.....	18
7.6 Sleep mode and wake-up.....	19
7.6.1 Entering the sleep mode.....	19
7.6.2 Wake-up.....	19
7.6.3 During a charge pause.....	20
7.7 Plug-out phase.....	20
8 Timings and constants	21
9 Matching EV — EVSE process	22
9.1 Overview.....	22
9.2 Initialization of matching process.....	24
9.3 Discovery of the connected low-layer communication module.....	24
9.4 Validation of matching decision.....	25
9.5 Set-up a logical network.....	27
9.6 Leave the logical network.....	27
9.7 Error handling.....	27

10 EMC requirements27

11 Signal coupling27

12 Layer 2 interfaces28

 12.1 Overview28

 12.2 Data SAP28

 12.3 Data link control SAP to layer 328

Annex A (normative) HomePlug Green PHY on control pilot line30

Annex B (informative) IEEE 1901.2 G3-PLC profile on control pilot line72

Bibliography79