

# ISO 17987-4:2016-09 (E)

## Road vehicles - Local Interconnect Network (LIN) - Part 4: Electrical physical layer (EPL) specification 12 V/24 V

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
Introduction .....		v
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms, definitions, symbols and abbreviated terms .....</b>	<b>1</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.2</b>	<b>Symbols .....</b>	<b>2</b>
<b>3.3</b>	<b>Abbreviated terms .....</b>	<b>5</b>
<b>4</b>	<b>Conventions .....</b>	<b>6</b>
<b>5</b>	<b>Electrical physical layer requirements .....</b>	<b>6</b>
<b>5.1</b>	<b>Bit rate deviation .....</b>	<b>6</b>
<b>5.1.1</b>	<b>12 V LIN systems: Parameters .....</b>	<b>6</b>
<b>5.1.2</b>	<b>24 V LIN systems: Parameters .....</b>	<b>7</b>
<b>5.2</b>	<b>Timing requirements .....</b>	<b>9</b>
<b>5.2.1</b>	<b>Bit timing .....</b>	<b>9</b>
<b>5.2.2</b>	<b>Synchronization procedure .....</b>	<b>9</b>
<b>5.2.3</b>	<b>Bit sample timing .....</b>	<b>9</b>
<b>5.3</b>	<b>Line driver/receiver .....</b>	<b>11</b>
<b>5.3.1</b>	<b>General configuration .....</b>	<b>11</b>
<b>5.3.2</b>	<b>Definition of supply voltages for the physical interface .....</b>	<b>11</b>
<b>5.3.3</b>	<b>Signal specification .....</b>	<b>12</b>
<b>5.3.4</b>	<b>12 V LIN systems: Electrical parameters .....</b>	<b>13</b>
<b>5.3.5</b>	<b>24 V LIN systems: Electrical parameters .....</b>	<b>17</b>
<b>5.3.6</b>	<b>Line characteristics .....</b>	<b>20</b>
<b>5.3.7</b>	<b>12 V LIN systems: performance in non-operation supply voltage range .....</b>	<b>20</b>
<b>5.3.8</b>	<b>24 V LIN systems: performance in non-operation supply voltage range .....</b>	<b>21</b>
<b>5.3.9</b>	<b>Performance during fault modes .....</b>	<b>21</b>
<b>5.3.10</b>	<b>ESD/EMI compliance .....</b>	<b>21</b>
<b>Annex A (informative)</b>	<b>LIN peripheral interface design considerations .....</b>	<b>22</b>
<b>Bibliography .....</b>		<b>27</b>