

ISO 6624-1:2017-04 (E)

Internal combustion engines - Piston rings - Part 1: Keystone rings made of cast iron

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative reference	1
3	Terms and definitions	1
4	Overview	1
5	Ring types and designation examples	1
5.1	Type T -- Straight faced keystone ring 6°	1
5.1.1	General features	1
5.1.2	Designation	2
5.2	Type TB -- Symmetrical barrel faced keystone ring 6°	2
5.2.1	General features	2
5.2.2	Designation	4
5.3	Type TBA -- Asymmetrical barrel faced keystone ring 6°	4
5.3.1	General features	4
5.3.2	Designation	5
5.4	Type TM -- Taper faced keystone ring 6°	5
5.4.1	General features	5
5.4.2	Designation	6
5.5	Type K -- Straight faced keystone ring 15°	7
5.5.1	General features	7
5.5.2	Designation	7
5.6	Type KB -- Symmetrical barrel faced keystone ring 15°	7
5.6.1	General features	7
5.6.2	Designation	8
5.7	Type KBA -- Asymmetrical barrel faced keystone ring 15°	8
5.7.1	General features	8
5.7.2	Designation	9
5.8	Type KM -- Taper faced keystone ring 15°	9
5.8.1	General features	9
5.8.2	Designation	10
6	Common features	11
6.1	Type T, TB, TBA, TM, K, KB, KBA, KM rings -- Inside chamfered edges (KI)	11
6.2	Type T, TB, TBA, TM, K, KB, KBA, KM rings (positive twist type) internal bevel or internal step top side	11
6.3	Type TM or KM rings with partly cylindrical machined (LM) or lapped (LP) peripheral surface	12
6.4	Type T, TB, TBA, TM, K, KB, KBA, KM rings -- Plating/coating configuration	13
6.4.1	Uncoated rings	13
6.4.2	Chromium plated, PVD coated or spray coated rings	14
7	Force factors	16
8	Dimensions	16
Bibliography		24