ISO 12619-10:2017-08 (E)

Road vehicles - Compressed gaseous hydrogen (CGH2) and hydrogen/natural gas blends fuel system components - Part 10: Pressure relief device (PRD)

Contents

Page

Foreword iv

1 Scope 1

2 Normative references 1

3 Termsanddefinitions 1

4 Marking 2

5 Construction and assembly 3

6 Tests 3
6.1 Applicability 3
6.2 Hydrostatic strength 4
6.2.1 Housing 4
6.2.2 Fusible material 4
6.3 Leakage 4
6.4 Bending moment 5
6.5 Continued operation 5
6.5.1 Test procedure 5
6.5.2 Requirements 5
6.6 Accelerated life 5
6.6.1 General 5
6.6.2 Test procedure 5
6.6.3 Accelerated-life test temperature 6
6.6.4 Requirements 6
6.7 Benchtop activation 6
6.7.1 General 6
6.7.2 Thermally activated relief devices 6
6.7.3 Parallel-combination relief devices 7
6.8 Thermal cycling 7
6.8.1 Test procedure 7
6.8.2 Requirements 8
6.9 Condensate-corrosion resistance 8
6.9.1 Test procedure 8
6.9.2 Test solution 8
6.10 Flow capacity 8
6.10.1 General 8
6.10.2 Test procedure 8
6.11 Impact due to drop and vibration 9
6.11.1 Impact due to drop 9
6.11.2 Vibration 9

7 Production batch inspection and acceptance testing 9

Annex A (normative) Determination of fusible material yield temperature and PRD activation temperature 10

Bibliography 12