

ISO 19377:2017-11 (E)

Heavy commercial vehicles and buses - Emergency braking on a defined path - Test method for trajectory measurement

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Principle	2
5	Variables	2
6	Measuring equipment	3
7	Test conditions	3
7.1	General	3
7.2	Test track and ambient conditions	4
7.3	Test vehicle	4
7.3.1	General vehicle condition	4
7.3.2	Loading condition	4
7.3.3	Number of test runs	4
8	Test methods	4
8.1	Test method for braking straight ahead	4
8.1.1	Initial driving condition	4
8.1.2	Definition of the desired path and track	4
8.1.3	System intervention	5
8.2	Test method for braking in a constant radius curve	5
8.2.1	Initial driving condition	5
8.2.2	Definition of the desired path and track	5
8.2.3	System intervention	6
9	Data evaluation and presentation of results	6
9.1	General	6
9.2	Characteristic values	7
9.2.1	Maximum path deviation, DP,max	7
9.2.2	Maximum rear axle path deviation, DPR,max	7
9.2.3	Maximum trailer path deviation, DPT,max	8
9.2.4	Deceleration at full braking	8
9.2.5	Maximum articulation angle(s) (optional)	8
9.2.6	Corrective steering action, H,C (for closed-loop test)	8
9.2.7	Indication of leaving the desired track (optional)	8
Annex A (normative)	Test report -- General data and test conditions	9
Annex B (informative)	Example of test reports	10
Bibliography		12