

# ISO 24102-6:2018 (E)

## Intelligent transport systems — Communications access for land mobiles (CALM) — ITS station management — Part 6: Path and flow management

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	Overview
5.1	Relation with the ITS station reference architecture
5.2	ITS-S flows
5.3	ITS-S communication profiles
5.4	ITS-S paths
5.5	ITS-S capabilities
5.6	Path and flow management
5.7	ITS station management functionalities
5.8	ITS station management information tables
5.9	Interaction with ITS station layers
6	Requirements for flow management and communication profile selection
6.1	ITS-S flow type parameters
6.2	ITS-S flow parameters
6.3	ITS-S flow monitoring
6.4	Notification of a communication profile determination
6.5	Processing request to provide communication profiles
6.6	Processing flow statistic reports
7	Requirements for flow registration
7.1	Processing ITS-S flow type registration from ITS-S-AP
7.2	Processing RegisterFlow from ITS-S-AP
7.3	Processing ReleaseFlow request from ITS-S-AP
7.4	Checking ITS-S-AP credentials
7.5	Checking communication requirements
7.6	Checking ITS-S path availability
7.7	Communication profile determination
8	Requirements for path management
8.1	ITS-S path parameters
8.2	Topological and geographic position parameters
8.3	Collecting topological and geographical information
8.4	Path management
8.5	ITS-S path monitoring
8.6	Interface management
9	Requirements for path selection
9.1	General requirements for path selection
9.2	Routing policies parameters
9.3	Notifying path selection
9.4	Notifying routing policies

- 10 Requirements for ITS-S capabilities management
  - 10.1 Maintenance of ITS-S capabilities information
  - 10.2 Determination of internal ITS-S capabilities
  - 10.3 Determination of neighbour ITS-S capabilities
  - 10.4 Activating ITS-S capabilities in the ITS-S Managed Service Entity
  - 10.5 Suspending ITS-S capabilities in the ITS-S Managed Service Entity
  - 10.6 Resuming ITS-S capabilities in the ITS-S Managed Service Entity
  - 10.7 Reporting about ITS-S capabilities in the ITS-S Managed Service Entity

**Annex A (normative) M\*-COMMANDs from SME**

- A.1 General
- A.2 Overview
- A.3 Details
  - A.3.1 AdjustFlows
  - A.3.2 CollectFlowStats
  - A.3.3 CollectPathStats
  - A.3.4 DiscoverCapa
  - A.3.5 GetCapa
  - A.3.6 SetCapa
  - A.3.7 SetCP
  - A.3.8 SetFlow2Path
  - A.3.9 SetFlowPolicy
  - A.3.10 SetPath

**Annex B (normative) M\*-REQUESTs to the SME**

- B.1 General
- B.2 Overview
- B.3 Details
  - B.3.1 GetCP
  - B.3.2 NotifyCapa
  - B.3.3 NotifyLocGeo
  - B.3.4 NotifyLocTopo
  - B.3.5 NotifyNeighbourCapa
  - B.3.6 NotifyPath
  - B.3.7 RegisterFlow
  - B.3.8 ReleaseFlow
  - B.3.9 ReportFlowStats
  - B.3.10 ReportPathStats

**Annex C (normative) PFM error codes**

**Annex D (normative) ASN-1 modules**

- D.1 Overview
- D.2 Module ITSpfm
- D.3 Dynamic extensions
  - D.3.1 M\*-SAP extensions of ISO 24102-3
  - D.3.2 ASN.1 CLASS types of ISO 24102-6
  - D.3.3 Other ASN.1 types