ISO 20762:2018 (E)

Electrically propelled road vehicles — Determination of power for propulsion of hybrid electric vehicle

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols and abbreviated terms

5 Test condition

- 5.1 Test instrumentation
- 5.1.1 Chassis dynamometer
- 5.1.2 Test room
- 5.1.3 Cooling fan
- 5.2 Measurement
- 5.2.1 Measurement items and accuracy
- 5.2.2 Measurement frequency

6 Test procedure

- 6.1 General
- 6.2 Preparation of chassis dynamometer
- 6.2.1 Roller
- 6.2.2 Tire slippage
- 6.2.3 Chassis dynamometer warm-up
- 6.2.4 Chassis dynamometer control
- 6.3 Preparation of vehicle
- 6.4 Preparation of measurement devices
- 6.5 Initial charge of RESS
- 6.6 Vehicle soak
- 6.7 Vehicle installation
- 6.8 Test sequence
- 6.8.1 General
- 6.8.2 Vehicle conditioning
- 6.8.3 RESS adjustment
- 6.8.4 Vehicle operation
- 6.8.5 Pedal operation
- 6.8.6 End of vehicle running
- 6.9 Calculation of HEV system power
- 6.9.1 General
- 6.9.2 Calculation for TP1
- 6.9.3 Calculation for TP2
- 6.9.3.1 Calculation
- 6.9.3.2 ICE power correction factors
- 6.9.3.3 Corrected HEV system power for test procedure option 2 (TP2)
- 6.10 Determination of maximum HEV system power

7 Test report

- 7.1 General
- 7.2 Calculated values based on measured data
- 7.3 Measured data

7.4 Environmental data
7.5 Assumed values
7.6 General vehicle data based on the manufacturer's information (informative)

Annex A (informative) Examples for gearbox system efficiency factor (includes gearbox and differential) at maximum HEV system power

A.1 General
A.2 Series hybrid-electric vehicle (Series HEV)
A.3 Parallel hybrid-electric vehicle (Parallel HEV)
A.4 Power split hybrid-electric vehicle (power split HEV)

Page count: 17