

ISO 19638:2018 (E)

Intelligent transport systems — Road boundary departure prevention systems (RBDPS) — Performance requirements and test procedures

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	Specifications and requirements
5.1	System function
5.2	Requirements
5.2.1	Functionality
5.2.2	State transition
5.2.2.1	State transition behaviour
5.2.2.1.1	Transition from off to on
5.2.2.1.2	Transition from on to off
5.2.2.1.3	RBDPS stand-by state
5.2.2.1.4	RBDPS active state
5.2.2.1.5	Transition from RBDPS stand-by to active
5.2.2.1.6	Transition from RBDPS active to stand-by
5.2.3	Driver interface and system reaction
5.2.3.1	System reaction
5.2.3.2	Display elements
5.2.3.3	State symbols
5.2.3.4	Manuals
5.2.3.5	User-adjustable function
5.2.4	Minimum functionality
5.2.4.1	Velocity for RBDPS operation
5.2.4.2	Lateral acceleration performance and longitudinal deceleration performance for RBDPS operation
5.2.4.3	Location for RBDPS operation
5.2.4.4	Operational limits
5.2.4.4.1	Operational limits of lateral acceleration and lateral jerk
5.2.4.4.2	Operational limits of active duration time
5.2.4.4.3	Operational limits of longitudinal deceleration
5.2.5	Failure reactions
6	Performance evaluation test methods
6.1	General
6.2	Environmental conditions
6.3	Test course conditions
6.4	Test vehicle conditions
6.5	Test system installation and configuration
6.6	Parameters recoverable from data record
6.7	Test track
6.8	Test procedure
6.8.1	Test 1: RBDPS basic performance test
6.8.1.1	Test conditions setup for Test 1
6.8.1.2	Test procedure for Test 1

- 6.8.1.3 Pass criteria for Test 1
- 6.8.2 Test 2: RBDPS deceleration performance test
 - 6.8.2.1 Test conditions for Test 2
 - 6.8.2.2 Test procedure for Test 2
 - 6.8.2.3 Pass criteria

Annex A (normative) Road boundaries by road type

Annex B (informative) Example curved track for the test procedure

Annex C (informative) Relationship between LDWS, LKAS, and RBDPS

Annex D (informative) Speed reduction performance summary

Page count: 19