

# ISO 15622:2018 (E)

## Intelligent transport systems — Adaptive cruise control systems — Performance requirements and test procedures

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	Classification
5.1	Type of ACC systems
6	Requirements
6.1	Basic control strategy
6.2	Functionality
6.2.1	Control modes
6.2.2	Stationary or slow moving targets
6.2.3	Following capability
6.2.3.1	General
6.2.3.2	Detection range on straight roads
6.2.3.3	Target discrimination
6.2.3.4	Curve capability
6.2.4	“Go” transition
6.3	Basic driver interface and intervention capabilities
6.3.1	Operation elements and system reactions
6.3.2	Display elements
6.3.3	Symbols
6.4	Operational limits
6.5	Activation of brake lights
6.6	Failure reactions
7	Performance evaluation test methods
7.1	Environmental conditions
7.2	Test target specification
7.2.1	General
7.2.2	Infrared LIDAR1 1 The test target is defined by a coefficient of a reflector: Target A represents at least 95 % of all vehicles driving on motorways. Target B represents the reflectivity of a dirty car without any retro reflector.
7.2.3	Millimetre wave RADAR2 2 The test target is defined by a Radar Cross Section (RCS) Target A at today known frequencies (60, 77, 90 GHz), represents at least 95 % of all vehicles driving on motorways. Target B is representative of a motorcycle.
7.3	Automatic “Stop” capability test for FSRA-type only
7.3.1	Test target vehicle
7.3.2	Initial conditions
7.3.3	Test procedure
7.4	Target acquisition range test
7.5	Target discrimination test
7.5.1	General
7.5.2	Initial conditions
7.5.3	Test procedure

- 7.6 Curve capability test
- 7.6.1 General
- 7.6.2 Test field
- 7.6.3 Curve capability, target vehicle
- 7.6.4 Driving scenario

**Annex A (normative) Technical information**

- A.1 LIDAR, coefficient of test target
- A.1.1 Solid angle,  $\Omega$
- A.1.2 Radiated intensity, I
- A.1.3 Intensity of irradiation, E
- A.1.4 Coefficient for test target CTT
- A.1.5 Reflector size
- A.2 Definition of the RCS of a corner cube type test target
- A.3 Following capability

Page count: 24