# ISO 13216-3:2018 (E)

## Road vehicles — Anchorages in vehicles and attachments to anchorages for child restraint systems — Part 3: Classification of child restraint system and space in vehicle

## Contents


Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Vehicle space requirements

- 4.1 Space required in a vehicle to accommodate specified types and installation modes of child restraint systems
- 4.1.1 General
- 4.1.2 Mass of CRF
- 4.1.3 Installation and assessment using virtual tools and procedures
- 4.2 Space required for full-height forward-facing toddler child restraint systems
- 4.3 Space required for reduced-height forward-facing toddler child restraint systems
- 4.4 Space required for reduced-height forward-facing toddler child restraint systems having a reduced contour in the upper part, and an extended seatback upper part
- 4.5 Space required for full-size rearward-facing toddler child restraint systems
- 4.6 Space required for reduced-size rearward-facing toddler child restraint systems
- 4.7 Space required for rearward-facing infant child restraint systems
- 4.8 Space required for lateral-facing infant child restraint system (carry-cot)
- 4.9 Space required for booster seat and booster cushion
- 4.9.1 Purpose of the booster system envelopes for determination of space and seat belt alignment in vehicles
- 4.9.2 Installation requirements
- 4.9.3 Belt routing requirements
- 4.9.4 Installation with ISOFIX support
- 4.9.5 Installation without ISOFIX support

5 Dimensions of child restraint system

- 5.1 Maximum dimensions of child restraint systems
- 5.2 Full-height forward-facing toddler child restraint system
- 5.3 Reduced-height forward-facing toddler child restraint system
- 5.4 Reduced-height forward-facing toddler child restraint systems with a reduced contour in the upper part, and an extended seatback upper part
- 5.5 Full-size rearward-facing toddler child restraint system
- 5.6 Reduced-size rearward-facing toddler child restraint system
- 5.7 Rearward-facing infant child restraint systems
- 5.8 Lateral-facing infant child restraint systems
- 5.9 Booster seat and booster cushion restraint systems
- 5.9.1 Purpose of the booster system envelopes with regard to child restraint systems
- 5.9.2 Maximum dimensional requirements
- 5.9.3 Booster with ISOFIX additional requirements
- 5.10 Procedure for checking CRS compliance with CRF
- 5.11 Installation and assessment using virtual tools and procedures

6 Classification system

Annex A (informative) Marking of vehicle seating positions and child restraint systems

**A.1 General**
**A.2 Marking of space for child seating positions in a vehicle**
**A.3 Marking of the type and size of a child restraint system**

**Annex B (informative) Drawings and tools**

**Page count: 26**