

ISO 12156-1:2018 (E)

Diesel fuel — Assessment of lubricity using the high-frequency reciprocating rig (HFRR) — Part 1: Test method

Contents

| | |
|---------|--|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Principle |
| 5 | Reagents and materials |
| 6 | Apparatus |
| 7 | Sampling |
| 8 | Preparation and calibration |
| 8.1 | Preparation of apparatus |
| 8.1.1 | Test plates and balls |
| 8.1.2 | Hardware |
| 8.2 | Calibration and correction |
| 8.2.1 | Temperature |
| 8.2.2 | Frequency |
| 8.2.3 | Stroke length |
| 8.2.4 | Test duration |
| 8.2.5 | Test rig performance |
| 9 | Test procedure |
| 10 | Measurement of wear scar |
| 10.1 | General |
| 10.2 | Method “A” — Digital camera |
| 10.3 | Method “B” — Visual observation |
| 11 | Test results |
| 12 | Precision |
| 12.1 | General |
| 12.2 | Repeatability, r |
| 12.3 | Reproducibility, R |
| 13 | Test report |
| Annex A | (informative) Measurement of HFRR wear scars |