

ISO 1496-5:2018 (E)

Series 1 freight containers — Specification and testing — Part 5: Platform and platform-based containers

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Dimensions and ratings
4.1	External dimensions
4.2	Internal dimensions
4.3	Ratings
5	Design requirements
5.1	General
5.2	Interlocked pile of folded containers
5.3	Corner fittings
5.4	Base structure
5.5	End structure (platform-based containers only)
5.6	Side structure (platform-based containers only)
5.7	Walls and securing devices
5.8	Door openings
5.9	Requirements — Optional features — Fork-lift pockets
6	Testing
6.1	General
6.2	Test No. 1 — Stacking
6.2.1	General
6.2.2	Procedure
6.2.2.1	Platform container
6.2.2.2	Platform-based container
6.2.2.3	Application of force
6.2.3	Requirements
6.3	Test No. 2 — Lifting from the four top corner fittings
6.3.1	General
6.3.2	Procedure
6.3.3	Requirements
6.4	Test No. 3 — Lifting from the four bottom corner fittings
6.4.1	General
6.4.2	Procedure
6.4.3	Requirements
6.5	Test No. 4 — External restraint (longitudinal)
6.5.1	General
6.5.2	Procedure
6.5.3	Requirements
6.6	Test No. 5 — Strength of end walls (where provided)7 7 Tests No. 5 and No. 6 are applicable to only some types of platform-based containers. Test No. 6 of ISO 1496-1:2013 (strength of side walls) is not applicable.
6.6.1	General
6.6.2	Procedure
6.6.3	Requirements
6.7	Test No. 6 — Strength of the roof (where provided)7)
6.7.1	General

- 6.7.2 Procedure
 - 6.7.3 Requirements
 - 6.8 Test No. 7 — Floor strength
 - 6.8.1 General
 - 6.8.2 Procedure
 - 6.8.3 Requirements
 - 6.9 Test No. 8 — Rigidity (transverse) (not applicable to platform containers)
 - 6.9.1 General
 - 6.9.2 Procedure
 - 6.9.3 Requirements
 - 6.10 Test No. 9 — Rigidity (longitudinal) (not applicable to platform containers)
 - 6.10.1 General
 - 6.10.2 Procedure
 - 6.10.3 Requirements
 - 6.11 Test No. 10 — Lifting from fork-lift pockets (where provided)
 - 6.11.1 General
 - 6.11.2 Procedure
 - 6.11.2.1 Containers fitted with one set of fork-lift pockets
 - 6.11.2.2 Containers fitted with two sets of fork-lift pockets
 - 6.11.3 Requirements
 - 6.12 Test No. 11 — Weatherproofness (where appropriate)^{12 12} For example, type P5 containers equipped with side curtains.
 - 6.12.1 Procedure
 - 6.12.2 Requirements
- 7 Testing of platform-based containers with incomplete superstructure in the folded condition (type codes P3 and P4 only) and of an interlocked pile of such containers
- 7.1 General
 - 7.2 Test No. 12 — Stacking (type codes P3 and P4 only)
 - 7.2.1 General
 - 7.2.2 Procedure
 - 7.2.3 Requirements
 - 7.3 Test No. 13 — Lifting of an interlocked pile by the top
 - 7.3.1 General
 - 7.3.2 Procedure
 - 7.3.3 Requirements
 - 7.4 Test No. 14 — Lifting of a flush folded container by the top
 - 7.4.1 General
 - 7.4.2 Procedure
 - 7.4.3 Requirements
- Annex A (normative) Diagrammatic representation of capabilities of platform and platform-based containers
- Annex B (normative) Dimensions of fork-lift pockets (where provided)
- Annex C (normative) Cargo-securing systems for platform and platform-based containers
- C.1 General
 - C.2 Design requirements
 - C.3 Testing
- Annex D (informative) Dimensions of existing 1CC, 1C and 1CX platform-based containers (type codes P1 to P4) for the carriage of small multimodal containers