

ISO 1496-2:2018 (E)

Series 1 freight containers — Specification and testing — Part 2: Thermal containers

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Classification
5	Marking
6	Dimensions and ratings
6.1	External dimensions
6.2	Internal dimensions
6.3	Ratings
7	Design requirements
7.1	General
7.2	Corner fittings
7.3	Base structure
7.4	End structure
7.5	Side wall structure
7.6	Walls
7.7	Door opening
7.8	Sanitary and taint-free requirements
7.9	Requirements for optional features
7.9.1	Fork-lift pockets
7.9.2	Gooseneck tunnels
7.9.3	Drains
7.9.4	Water connections
7.9.5	Picture frames
7.9.6	Modified/controlled atmospheres
7.9.7	Fresh air ventilation control
7.9.8	Humidity control
7.9.9	Load line
7.9.10	Floor
7.9.11	Air circulation
8	Testing
8.1	General
8.2	Test No. 13 — Airtightness test
8.2.1	General
8.2.2	Procedure
8.2.3	Requirements
8.3	Test No. 14 — Heat leakage test
8.3.1	General
8.3.2	Procedure
8.3.3	Heat leakage calculation
8.3.4	Requirements
8.4	Test No. 15 a) — Test of the performance of a thermal container under refrigeration by a mechanical refrigeration unit (MRU)
8.4.1	General

8.4.2	Test conditions
8.4.3	Test procedure
8.4.4	Requirements
8.5	Test No. 15 b) — Functional test of a thermal container at high ambient temperatures while being cooled by a mechanical refrigeration unit (MRU)
8.5.1	General
8.5.2	The thermal container shall be equipped with instruments for the measurement of:
8.5.3	Test conditions
8.5.4	Test procedure
8.5.5	Requirements
8.6	Test No. 15 c) — Energy consumption of a thermal container at defined ambient temperatures while being cooled by a mechanical refrigeration unit (MRU)
8.6.1	General
8.6.2	The thermal container shall be equipped with instruments for the measurement of:
8.6.3	Test conditions
8.6.4	Test procedure
8.6.5	Requirements
8.7	Test No. 16 — Strength of mounting devices for removable equipment (where fitted)
8.7.1	General
8.7.2	Test No. 16 a) — Vertical loading
8.7.2.1	General
8.7.2.2	Procedure
8.7.2.3	Requirements
8.7.3	Test No. 16 b) — Horizontal loading
8.7.3.1	General
8.7.3.2	Procedure
8.7.3.3	Requirements
9	Electrical aspects of thermal containers
9.1	General
9.2	General requirements for standard voltage equipment
9.3	Remote condition monitoring
Annex A	(normative) Requirements for cooling water connections
Annex B	(informative) Picture frames
Annex C	(normative) Air temperature measurement points
Annex D	(normative) Phase connections to container plugs and sockets
Annex E	(normative) Electric plug and socket, four-pin, 380/440 V, 50/60 Hz, 32 A
Annex F	(informative) Electrical power supplies for thermal containers (9.2)
Annex G	(normative) General requirements for 220 V and dual voltage equipment
G.1	220 V equipment
G.2	Dual voltage equipment
Annex H	(informative) MRU Nose Mounted Frame (Optional Backup Generator Set)
Annex I	(informative) Ageing of polyurethane foam
I.1	General
I.2	Background
I.3	Determination of accelerated aged value of thermal conductivity
I.4	Calculation method for the determination of the thermal transmittance of a panel (U _{d,s})
I.5	Calculating ageing
I.6	Conclusion