ISO 19825:2018 (E)

Road vehicles — Liquefied petroleum gas (LPG) refuelling connector

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 General construction requirements

5 Nozzles

6 Standard receptacle dimensions J15 and K15

7 Receptacles

8 Instructions

9 Marking

10 Tests

10.1 General requirements
10.2 Impact resistance
10.2.1 Nozzle test
10.2.2 Receptacle test
10.3 Leakage at room temperature
10.4 Abnormal loads
10.4.1 General
10.4.2 Testing the unpressurised condition
10.4.3 Testing the pressurised condition
10.5 Mounting hardware torque
10.6 Leakage at low and high temperatures
10.7 Nozzle freezing
10.8 Durability
10.8.1 Endurance
10.8.1.1 General
10.8.1.2 Nozzle test
10.8.1.3 Receptacle test
10.8.1.4 Receptacle check valve test
10.8.2 Corrosion resistance
10.8.2.1 Nozzle test
10.8.2.2 Receptacle test
10.8.2.3 Test procedure
10.8.3 Brass material compatibility
10.8.4 Resistance to dry heat
10.8.5 Ozone ageing
10.8.6 Temperature cycle
10.8.7 Compatibility with Liquefied Petroleum Gas
10.8.8 Electrical continuity
10.9 Overpressure
10.10 Oxygen ageing
10.11 Non-metallic material immersion

10.12 Vibration resistance
10.13 Creep
10.14 Automotive fluid exposure
10.14.1 General
10.14.2 Test method
10.14.3 Fluids
10.14.4 Pass criteria

Annex A (normative) Critical dimensions of the nozzles

Annex B (informative) Manufacturing and production test plan

B.1 Acceptance of the manufacturing and production plan
B.2 Qualification
B.3 Leakage test
B.4 Additional tests
B.5 Evaluation

Page count: 21