

ISO 11452-2:2019 (E)

Road vehicles — Component test methods for electrical disturbances from narrowband radiated electromagnetic energy — Part 2: Absorber-lined shielded enclosure

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Test conditions
5	Test location
6	Test apparatus and instrumentation
6.1	General
6.2	Measuring equipment
6.3	Stimulation and monitoring of DUT
7	Test set-up for DUT powered by an unshielded power system
7.1	Ground plane
7.2	Power supply and AN
7.3	Location of DUT
7.4	Location of test harness
7.5	Location of load simulator
7.6	Location of field generating device (antenna)
8	Test setup for DUT powered by a shielded power system
8.1	Ground plane
8.2	Power supply and AN
8.3	Location of DUT
8.4	Location of test harness
8.5	Location of load simulator
8.6	Location of field generating device (antenna)
9	Test method
9.1	General
9.2	Test plan
9.3	Test procedure
9.3.1	General
9.3.2	Substitution method
9.3.3	Field calibration
9.3.4	DUT test
9.4	Test report
Annex A	(informative) Remote/local grounding
A.1	DUT remotely grounded
A.2	DUT locally grounded
Annex B	(informative) Function performance status classification (FPSC)
B.1	General
B.2	Classification of test severity level
B.3	Example of FPSC application using test severity levels