

# ISO 19642-3:2019 (E)

## Road vehicles — Automotive cables — Part 3: Dimensions and requirements for 30 V a.c. or 60 V d.c. single core copper conductor cables

---

### Contents

|         |                                                                   |
|---------|-------------------------------------------------------------------|
|         | Foreword                                                          |
|         | Introduction                                                      |
| 1       | Scope                                                             |
| 2       | Normative references                                              |
| 3       | Terms and definitions                                             |
| 4       | Specifications                                                    |
| 4.1     | General test conditions                                           |
| 4.2     | Safety concerns                                                   |
| 4.3     | Voltage rating                                                    |
| 4.4     | Temperature classes                                               |
| 4.5     | Conductor material                                                |
| 4.6     | Conductors                                                        |
| 4.7     | Insulation thickness                                              |
| 4.8     | Cable outside diameter                                            |
| 4.9     | Representative conductor sizes for testing                        |
| 4.10    | Reference and requirements for the tests according to ISO 19642-2 |
| 5       | Requirements                                                      |
| 5.1     | General                                                           |
| 5.2     | Dimensional tests                                                 |
| 5.2.1   | Cable outside diameter                                            |
| 5.2.2   | Insulation thickness                                              |
| 5.2.3   | Conductor diameter                                                |
| 5.2.4   | Cross-sectional area (CSA)                                        |
| 5.2.5   | In-process cable outside diameter                                 |
| 5.3     | Electrical tests                                                  |
| 5.3.1   | Conductor resistance                                              |
| 5.3.2   | Requirement for determination of temperature coefficients         |
| 5.3.3   | Withstand voltage                                                 |
| 5.3.4   | Withstand voltage after environmental testing                     |
| 5.3.5   | Insulation faults                                                 |
| 5.3.6   | Insulation volume resistivity                                     |
| 5.4     | Mechanical tests                                                  |
| 5.4.1   | Strip force                                                       |
| 5.4.2   | Abrasion                                                          |
| 5.4.2.1 | General                                                           |
| 5.4.2.2 | Sandpaper abrasion test                                           |
| 5.4.2.3 | Scrape abrasion test                                              |
| 5.4.3   | Breaking force of the finished cable                              |
| 5.4.4   | Cyclic bending                                                    |
| 5.4.5   | Flexibility test                                                  |
| 5.5     | Environmental tests                                               |
| 5.5.1   | Test specimen preparation and winding tests                       |
| 5.5.2   | Long term heat ageing, 3 000 h at temperature class rating        |
| 5.5.3   | Short term heat ageing, 240 h at temperature class rating +25 °C  |
| 5.5.4   | Thermal overload, 6 h at temperature class rating +50 °C          |
| 5.5.5   | Pressure test at high temperature                                 |
| 5.5.6   | Shrinkage by heat                                                 |

- 5.5.7 Low temperature winding
- 5.5.8 Cold impact
- 5.5.9 Temperature and humidity cycling
- 5.5.10 Resistance to hot water
- 5.5.11 Resistance to liquid chemicals
- 5.5.12 Durability of cable marking
- 5.5.13 Stress cracking resistance
- 5.5.14 Resistance to ozone
- 5.5.15 Resistance to flame propagation

**Annex A (informative) ISO conductor sizes, number of strands and strand diameters**

- A.1 Conductors — Existing stranding configurations
- A.2 Conductors — Preferred stranding configurations

**Page count: 16**