

ISO 1496-3:2019 (E)

Series 1 freight containers — Specification and testing — Part 3: Tank containers for liquids, gases and pressurized dry bulk

Contents

| | |
|-------|-----------------------------------------------------------|
| | Foreword |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Dimensions and ratings |
| 4.1 | External dimensions |
| 4.2 | Ratings |
| 5 | Design requirements |
| 5.1 | General |
| 5.2 | Corner fittings |
| 5.2.1 | General |
| 5.2.2 | Doubler plates |
| 5.3 | Base structure |
| 5.4 | End structure |
| 5.5 | Side structure |
| 5.6 | Tank |
| 5.6.1 | Design and construction |
| 5.6.2 | Corrosion allowance |
| 5.6.3 | Tank openings |
| 5.6.4 | Pressure and vacuum relief devices |
| 5.6.5 | Inspection and maintenance openings |
| 5.6.6 | Gauging devices |
| 5.6.7 | Sealing (customs requirements) |
| 5.7 | Optional features |
| 5.7.1 | Gooseneck tunnels |
| 5.7.2 | Walkways |
| 5.7.3 | Ladders |
| 5.7.4 | Tank insulation |
| 5.7.5 | Tank heating and refrigeration |
| 6 | Testing |
| 6.1 | General |
| 6.2 | Test No. 1 — Stacking |
| 6.2.1 | General |
| 6.2.2 | Procedure |
| 6.2.3 | Requirements |
| 6.3 | Test No. 2 — Lifting from the four top corner fittings |
| 6.3.1 | General |
| 6.3.2 | Procedure |
| 6.3.3 | Requirements |
| 6.4 | Test No. 3 — Lifting from the four bottom corner fittings |
| 6.4.1 | General |
| 6.4.2 | Procedure |
| 6.4.3 | Requirements |
| 6.5 | Test No. 4 — External restraint (longitudinal) |
| 6.5.1 | General |
| 6.5.2 | Procedure |
| 6.5.3 | Requirements |

- 6.6 Test No. 5 — Internal restraint (longitudinal) (dynamic)
 - 6.6.1 General
 - 6.6.2 Procedure
 - 6.6.3 Requirements
- 6.7 Test No. 6 — Internal restraint (lateral)
 - 6.7.1 General
 - 6.7.2 Procedure
 - 6.7.3 Requirements
- 6.8 Test No. 7 — Rigidity (transverse)
 - 6.8.1 General
 - 6.8.2 Procedure
 - 6.8.3 Requirements
- 6.9 Test No. 8 — Rigidity (longitudinal)
 - 6.9.1 General
 - 6.9.2 Procedure
 - 6.9.3 Requirements
- 6.10 Test No. 9 — Load-transfer area test
 - 6.10.1 General
 - 6.10.2 Procedure
 - 6.10.3 Requirements
- 6.11 Test No. 10—Walkways (where provided)
 - 6.11.1 General
 - 6.11.2 Procedure
 - 6.11.3 Requirements
- 6.12 Test No. 11 — Ladders (where provided)
 - 6.12.1 General
 - 6.12.2 Procedure
 - 6.12.3 Requirements
- 6.13 Test No. 12 — Pressure test
 - 6.13.1 General
 - 6.13.2 Procedure
 - 6.13.3 Requirements

7 Identification and marking

Annex A (normative) Diagrammatic representation of capabilities appropriate to all types and sizes of tank containers, except where otherwise stated

Annex B (normative) Dynamic longitudinal impact test

- B.1 Test sample
- B.2 Test apparatus
 - B.2.1 Test platform
 - B.2.2 Impact creation
 - B.2.3 Measuring/recording system
 - B.2.3.1 General
 - B.2.3.2 Apparatus
 - B.2.4 Procedure
 - B.2.5 Analysis/processing of data
 - B.2.5.1 Data reduction system
 - B.2.5.2 Method for scaling measured acceleration versus time history values to compensate for under or over mass containers.
 - B.2.6 Defective accelerometer signal
 - B.2.7 Optional test method
 - B.2.8 Recording of data

Page count: 25