

# ISO 20766-9:2019 (E)

## Road vehicles — Liquefied petroleum gas (LPG) fuel systems components — Part 9: Pressure relieve device (PRD)

---

### Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Markings
5	Construction and assembly
6	Tests
6.1	Applicability
6.2	Hydrostatic strength
6.3	Leakage
6.4	Bending moment
6.5	Continued operation
6.5.1	Test procedure
6.5.2	Requirements
6.6	Accelerated life
6.6.1	General
6.6.2	Test procedure
6.6.3	Accelerated-life test temperature
6.6.4	Requirements
6.7	Benchtop activation
6.7.1	General
6.7.2	Thermally-activated relief devices
6.7.2.1	Test setup
6.7.2.2	Test procedure
6.7.2.3	Requirements
6.8	Thermal cycling
6.8.1	Test procedure
6.8.2	Requirements
6.9	Condensate-corrosion resistance
6.9.1	Test procedure
6.9.2	Test solution
6.10	Flow capacity
6.10.1	General
6.10.2	Test procedure
7	Production batch inspection and acceptance testing
Annex A	(normative) Determination of fusible material yield temperature and PRD activation temperature
A.1	General
A.2	Fusible material yield temperature
A.2.1	Sample selection
A.2.2	Test setup
A.2.3	Test procedure
A.2.4	Requirements
A.3	PRD activation temperature determination
A.3.1	Differential scanning calorimetry (DSC) method