ISO 21219-4:2019 (E)

Intelligent transport systems — Traffic and travel information (TTI) via transport protocol experts group, generation 2 (TPEG2) — Part 4: UML to XML conversion rules

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Abbreviated terms

5 Rules for UML to XML format description conversion

- 5.1 Definition of XML format description
- 5.2 The tpegML schema definition
- 5.3 The tpegML xml file definition
- 5.4 XML data type ranges
- 5.5 Abstract data types
- 5.6 TPEG standard tables
- 5.7 Application tables (stereotype <<enumeration>>)
- 5.8 Switching tables
- 5.9 Stereotype <<external>>
- 5.9.1 TPEG application <<external>> type
- 5.9.2 Non-TISA <<external>> XML schema
- 5.9.3 Non-TISA <<external>> binary type
- 5.10 Compound data types
- 5.10.1 Rule 1 — Classes
- 5.10.2 Rule 2 — Root element
- 5.10.3 Rule 3 — Attributes
- 5.10.3.1 Rule 3a — Datatypes
- 5.10.3.2 Rule 3b — Ordering
- 5.10.3.3 Rule 3c — Single multiplicity [minOccurs = 1..maxOccurs = 1]
- 5.10.3.4 Rule 3d — Multiplicity [minOccurs = 0..maxOccurs = 1], Multiplicity [minOccurs = 0.. maxOccurs > 1] and Multiplicity [minOccurs = 1.. maxOccurs > 1]
- 5.10.3.5 Rule 3e — Attributes stereotyped with <<OrderedComponentGroup>> or <<UnorderedComponentGroup>>
- 5.10.4 Rule 4 — Specialisations/Abstract classes
- 5.10.4.1 Rule 4a — Inheritance
- 5.10.4.2 Rule 4b — Switching
- 5.11 Example

Annex A (normative) TPEG Data Types schema definition

- A.1 Schema definition
- A.2 Abstract data types
- A.3 TPEG standard tables

Page count: 40