

# ISO 16505:2019-07 (E)

## Road vehicles - Ergonomic and performance aspects of Camera Monitor Systems - Requirements and test procedures

---

<b>Contents</b>		<b>Page</b>
Foreword .....		v
Introduction .....		vi
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>3.1</b>	<b>Vehicle related terms and definitions .....</b>	<b>1</b>
<b>3.2</b>	<b>Mirror related terms and definitions .....</b>	<b>2</b>
<b>3.3</b>	<b>Camera related terms and definitions .....</b>	<b>12</b>
<b>3.4</b>	<b>Monitor related terms and definitions .....</b>	<b>15</b>
<b>3.5</b>	<b>Camera Monitor System based terms and definitions .....</b>	<b>23</b>
<b>4</b>	<b>Symbols and abbreviated terms .....</b>	<b>33</b>
<b>5</b>	<b>General information and use case definitions .....</b>	<b>36</b>
<b>6</b>	<b>Requirements .....</b>	<b>40</b>
<b>6.1</b>	<b>System documentation .....</b>	<b>40</b>
<b>6.2</b>	<b>Intended use .....</b>	<b>41</b>
<b>6.2.1</b>	<b>Default view .....</b>	<b>41</b>
<b>6.2.2</b>	<b>Adjusted default view .....</b>	<b>41</b>
<b>6.2.3</b>	<b>Temporary modified view .....</b>	<b>41</b>
<b>6.2.4</b>	<b>Luminance and contrast adjustment .....</b>	<b>42</b>
<b>6.2.5</b>	<b>Overlays .....</b>	<b>42</b>
<b>6.3</b>	<b>Operating readiness (system availability) .....</b>	<b>42</b>
<b>6.4</b>	<b>Field of view .....</b>	<b>43</b>
<b>6.5</b>	<b>Magnification and resolution .....</b>	<b>43</b>
<b>6.5.1</b>	<b>Average magnification factor .....</b>	<b>43</b>
<b>6.5.2</b>	<b>Minimum magnification factor .....</b>	<b>43</b>
<b>6.5.3</b>	<b>Resolution (MTF) .....</b>	<b>44</b>
<b>6.6</b>	<b>Magnification aspect ratio .....</b>	<b>45</b>
<b>6.7</b>	<b>Monitor integration inside the vehicle .....</b>	<b>45</b>
<b>6.8</b>	<b>Image quality .....</b>	<b>46</b>
<b>6.8.1</b>	<b>Monitor isotropy .....</b>	<b>46</b>
<b>6.8.2</b>	<b>Luminance and contrast rendering .....</b>	<b>47</b>
<b>6.8.3</b>	<b>Colour rendering .....</b>	<b>47</b>
<b>6.8.4</b>	<b>Artefacts .....</b>	<b>48</b>
<b>6.8.5</b>	<b>Sharpness and depth of field .....</b>	<b>49</b>
<b>6.8.6</b>	<b>Geometric distortion .....</b>	<b>49</b>
<b>6.8.7</b>	<b>Further image quality requirements .....</b>	<b>50</b>
<b>6.9</b>	<b>Time behaviour .....</b>	<b>50</b>
<b>6.9.1</b>	<b>Frame rate .....</b>	<b>50</b>
<b>6.9.2</b>	<b>Image formation time .....</b>	<b>50</b>
<b>6.9.3</b>	<b>System latency .....</b>	<b>50</b>
<b>6.10</b>	<b>Failure behaviour .....</b>	<b>50</b>
<b>6.11</b>	<b>Quality and further ergonomic requirements .....</b>	<b>50</b>
<b>6.11.1</b>	<b>Needs of older persons .....</b>	<b>51</b>
<b>6.12</b>	<b>Influences from weather and environment .....</b>	<b>51</b>

<b>7</b>	<b>Test methods</b>	<b>51</b>
7.1	System documentation	51
7.2	Intended use	51
7.2.1	Default view	51
7.2.2	Adjusted default view	51
7.2.3	Temporary modified view	52
7.2.4	Luminance and contrast adjustment	52
7.2.5	Overlays	52
<b>7.3</b>	<b>Operating readiness (system availability)</b>	<b>52</b>
7.4	Field of view	54
7.5	Magnification and resolution	54
7.5.1	Average magnification factor	54
7.5.2	Minimum magnification factor	55
7.5.3	Resolution (MTF)	57
7.6	Magnification aspect ratio	60
7.7	Monitor integration inside the vehicle	60
7.8	Image quality	61
7.8.1	Monitor isotropy	61
7.8.2	Luminance and contrast rendering	63
7.8.3	Colour rendering	71
7.8.4	Artefacts	74
7.8.5	Sharpness, resolution, and depth of field	75
7.8.6	Geometric distortion	77
7.8.7	Further Image quality requirements	77
7.9	Time behaviour	77
7.9.1	Frame rate	77
7.9.2	Image formation time	77
7.9.3	System latency	77
7.10	Failure behaviour	78
7.11	Quality and further ergonomic requirements	79
7.11.1	Needs of older persons	79
7.12	Influences from weather and environment	79
<b>8</b>	<b>Functional safety</b>	<b>79</b>
<b>Annex A (normative)</b>	<b>Standard application on UN Regulation No. 46 class II and IV mirrors in commercial vehicles</b>	<b>80</b>
<b>Annex B (informative)</b>	<b>Formula applications, explanations, and guidelines</b>	<b>85</b>
<b>Annex C (informative)</b>	<b>Calculation of the dimensional magnification and of a correction factor to obtain the angular magnification</b>	<b>120</b>
<b>Annex D (informative)</b>	<b>Complementary information for resolution measurement</b>	<b>125</b>
<b>Annex E (informative)</b>	<b>Correlation between Resolution (MTF) and spatial frequency measured using SFR method for depth of field evaluation or sharpness evaluation</b>	<b>134</b>
<b>Annex F (informative)</b>	<b>Complementary charts and method for long distance measurements</b>	<b>139</b>
<b>Annex G (informative)</b>	<b>Distortion measurement</b>	<b>142</b>
<b>Bibliography</b>		<b>149</b>