

# ISO 6626-3:2019 (E)

## Internal combustion engines — Piston rings — Part 3: Coil-spring-loaded oil control rings made of steel

---

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms, definitions and symbols
3.1	Symbols
4	Piston ring types and designation examples
4.1	Type SOR — Steel oil control rings with R-shaped groove
4.1.1	General features and dimensions
4.1.2	Designation
4.2	Type SOV — Steel oil control rings with V-shaped groove
4.2.1	General features and dimensions
4.2.2	Designation
5	Common features
5.1	Ring width $h_1$ and radial wall thickness $a_1$
5.2	Land width $h_5$
5.3	Land angle $\alpha$ , $\beta$
5.4	Land spacing $B_3$
5.5	Slot sizes
5.6	Nitrided surface
5.7	PVD coating thickness of peripheral surface
5.8	Nominal contact pressure and tangential force
5.8.1	Nominal contact pressure
5.8.2	Actual tangential force, $F_t$ , and tolerance
5.8.3	Normalized tangential force, $FN$
5.9	Tolerance of tangential force $F_t$
6	Coil springs
6.1	Types of coil spring
6.2	Coil-spring excursion (extended gap)
6.3	Position of coil spring gap and fixing
6.4	Material
7	Type SOR
8	Type SOV
9	Dimensions