ISO 6626-3:2019 (E)

Internal combustion engines — Piston rings — Part 3: Coil-spring-loaded oil control rings made of steel

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms, definitions and symbols

3.1 Symbols

4 Piston ring types and designation examples

4.1 Type SOR — Steel oil control rings with R-shaped groove
4.1.1 General features and dimensions
4.1.2 Designation
4.2 Type SOV — Steel oil control rings with V-shaped groove
4.2.1 General features and dimensions
4.2.2 Designation

5 Common features

5.1 Ring width h1 and radial wall thickness a1
5.2 Land width h5
5.3 Land angle α, β
5.4 Land spacing B3
5.5 Slot sizes
5.6 Nitrided surface
5.7 PVD coating thickness of peripheral surface
5.8 Nominal contact pressure and tangential force
5.8.1 Nominal contact pressure
5.8.2 Actual tangential force, Ft, and tolerance
5.8.3 Normalized tangential force, FN
5.9 Tolerance of tangential force Ft

6 Coil springs

6.1 Types of coil spring
6.2 Coil-spring excursion (extended gap)
6.3 Position of coil spring gap and fixing
6.4 Material

7 Type SOR

8 Type SOV

9 Dimensions

Page count: 26