# ISO 17987-8:2019-10 (E)

## Road vehicles - Local Interconnect Network (LIN) - Part 8: Electrical physical layer (EPL) specification: LIN over DC powerline (DC-LIN)

## Contents

Page


Foreword ..... iv

Introduction ..... v

1 Scope ..... 1

2 Normative references ..... 1

3 Terms, definitions, symbols, and abbreviated terms ..... 1
3.1 Terms and definitions ..... 2
3.2 Symbols and abbreviated terms ..... 2

4 Electrical physical layer requirements ..... 5
4.1 General ..... 5
4.2 Transmitter characteristics ..... 6
4.2.1 Transmit signal specification ..... 6
4.2.2 Byte field modulation scheme ..... 7
4.2.3 Break field modulation scheme ..... 14
4.2.4 Wake-up signal modulation scheme ..... 15
4.3 Timing requirements ..... 18
4.3.1 Bit rate tolerance ..... 18
4.3.2 Bit timing ..... 19
4.3.3 Bit sample timing ..... 19
4.3.4 TXD assert timeout event ..... 19
4.3.5 Delay between transmitted byte field (DC-LIN node A) and received byte field (DC-LIN node A) ..... 19
4.3.6 Delay between transmitted byte field (DC-LIN node A) and received byte field (DC-LIN node B) ..... 19
4.4 Receiver characteristics ..... 21
4.5 Electrical parameters ..... 21
4.5.1 General configuration -- Coupling to the DC powerline ..... 21
4.5.2 Signal specification ..... 22
4.5.3 Line-out monitoring ..... 23
4.5.4 ESD compliance ..... 28
4.6 Communication in the presence of faults ..... 28

Annex A (informative) DC-LIN EPL peripheral interface design considerations ..... 30

Annex B (normative) DC-LIN EPL conformance test plan ..... 31

Bibliography ..... 56