

# ISO 8820-8:2019-10 (E)

## Road vehicles - Fuse-links - Part 8: Fuse-links with bolt-in contacts (Type H and J) with rated voltage of 450 V

---

<b>Contents</b>		<b>Page</b>
Foreword .....		iv
<b>1</b>	<b>Scope .....</b>	<b>1</b>
<b>2</b>	<b>Normative references .....</b>	<b>1</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>1</b>
<b>4</b>	<b>Marking, labelling and colour coding .....</b>	<b>1</b>
<b>5</b>	<b>Tests and requirements .....</b>	<b>2</b>
5.1	General .....	2
5.1.1	Test criteria .....	2
5.1.2	Test sequence .....	2
5.1.3	Test cable sizes .....	2
5.2	Voltage drop .....	3
5.2.1	Tests .....	3
5.2.2	Requirements .....	3
5.3	Transient current cycling .....	4
5.3.1	Test .....	4
5.3.2	Requirements .....	4
5.4	Environmental conditions .....	4
5.5	Operating time-rating .....	4
5.5.1	Test .....	4
5.5.2	Requirement .....	5
5.6	Current steps .....	5
5.7	Breaking capacity .....	5
5.7.1	Test .....	5
5.7.2	Requirement .....	5
5.8	Strength of terminals .....	5
5.8.1	Test .....	5
5.8.2	Requirements .....	6
5.9	Temperature rise .....	6
5.9.1	Test .....	6
5.9.2	Requirement .....	6
5.10	Resistance against temperature shock .....	6
5.10.1	Test .....	6
5.10.2	Requirement .....	7
<b>6</b>	<b>Dimensions .....</b>	<b>7</b>
6.1	Type H .....	7
6.2	Type J .....	8
<b>7</b>	<b>Test fixture for fuse-links Type H and Type J .....</b>	<b>9</b>
<b>Annex A (informative)</b>	<b>Classification .....</b>	<b>10</b>
<b>Bibliography .....</b>		<b>11</b>