

ISO 8820-8:2019-10 (E)

Road vehicles - Fuse-links - Part 8: Fuse-links with bolt-in contacts (Type H and J) with rated voltage of 450 V

Contents	Page
Foreword	iv
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Marking, labelling and colour coding	1
5 Tests and requirements	2
5.1 General	2
5.1.1 Test criteria	2
5.1.2 Test sequence	2
5.1.3 Test cable sizes	2
5.2 Voltage drop	3
5.2.1 Tests	3
5.2.2 Requirements	3
5.3 Transient current cycling	4
5.3.1 Test	4
5.3.2 Requirements	4
5.4 Environmental conditions	4
5.5 Operating time-rating	4
5.5.1 Test	4
5.5.2 Requirement	5
5.6 Current steps	5
5.7 Breaking capacity	5
5.7.1 Test	5
5.7.2 Requirement	5
5.8 Strength of terminals	5
5.8.1 Test	5
5.8.2 Requirements	6
5.9 Temperature rise	6
5.9.1 Test	6
5.9.2 Requirement	6
5.10 Resistance against temperature shock	6
5.10.1 Test	6
5.10.2 Requirement	7
6 Dimensions	7
6.1 Type H	7
6.2 Type J	8
7 Test fixture for fuse-links Type H and Type J	9
Annex A (informative) Classification	10
Bibliography	11