ISO 17536-4:2019-11 (E)

Road Vehicles - Aerosol separator performance test for internal combustion engines - Part 4: Laboratory fractional efficiency test method

Contents

Page

Foreword v

Introduction vi

1 Scope 1

2 Normative references 1

3 Terms, definitions, and abbreviated terms 1
3.1 Terms and definitions 1
3.2 Abbreviated terms 2

4 Measurement accuracy 2

5 Test materials and conditions 2
5.1 Absolute filter, wall flow trap and leakage 2
5.2 Test temperature 2
5.3 Test conditions 2

6 Test procedure 3
6.1 General 3
6.2 Test equipment 3
6.3 Aerosol generator 4
6.4 Aerosol sampling system 4
6.5 Particle sizing and counting monitor(s) 5

7 Apparatus qualification testing 5
7.1 Test stand verification 5
7.2 Concentration limit of the particle instrument 6
7.3 100 % efficiency test and development of purge time 6
7.4 Correlation test 6
7.5 Test duct air leakage test 6
7.6 Apparatus maintenance 7

8 Fractional efficiency test 7
8.1 General 7
8.1.1 New state (if possible) 7
8.1.2 Conditioned state as per ISO/TS 17536-2 7
8.2 Method 7
8.3 Calculations 7
8.4 Correlation and tare 7
8.5 Fractional efficiency test 8

9 Calculations and data acceptance criteria 9
9.1 Symbols used in following formulae 9
9.2 Symbols 9
9.3 Subscripts used in the following formulae 9
9.4 Average used in the following formulae 9
9.5 Test sampling 9
9.6 Correlation ratio 11
9.7 Penetration / Fractional efficiency 12

9.8 Efficiency 12
9.9 Data reduction 12
9.9.1 Correlation ratio data reduction 12
9.9.2 Correlation ratio data acceptance criteria 15
9.9.3 Penetration data reduction 15
9.9.4 Penetration Data Acceptance Criteria 17
9.9.5 Penetration maximum background counts 18
9.9.6 Penetration minimum upstream counts 18
9.9.7 Efficiency 18

Annex A (normative) Poisson statistics 19

Annex B (informative) Aerosol separator laboratory fractional efficiency test report 21

Annex C (normative) Test equipment 23

Bibliography 25