

# ISO 6621-5:2020-01 (E)

## Internal combustion engines - Piston rings - Part 5: Quality requirements

---

<b>Contents</b>		<b>Page</b>
	<b>Foreword</b> .....	<b>iv</b>
	<b>Introduction</b> .....	<b>v</b>
<b>1</b>	<b>Scope</b> .....	<b>1</b>
<b>2</b>	<b>Normative references</b> .....	<b>1</b>
<b>3</b>	<b>Terms and definitions</b> .....	<b>1</b>
<b>4</b>	<b>Visible defects</b> .....	<b>2</b>
4.1	General.....	2
4.2	Pores, cavities and sand inclusions.....	2
4.3	Scratches, indentations, depressions and cracks.....	2
4.3.1	Scratches.....	2
4.3.2	Indentations, depressions.....	3
4.3.3	Cracks.....	3
4.4	Edges.....	3
4.4.1	Edge configuration.....	3
4.4.2	Chipping and similar defects on peripheral edges and peripheral edges at the gap.....	4
4.4.3	Chipping and defects on non-peripheral edges.....	8
4.4.4	Chipping and defects on inside gap corners.....	8
4.5	Other characteristics subject to visual inspection only.....	9
4.5.1	Discolouring or staining of surface.....	9
4.5.2	Casting skin and deposits on inside surface.....	9
4.5.3	Chipping on uncoated surfaces.....	9
4.5.4	Chromium plated peripheral surface.....	9
4.5.5	Spray coatings.....	9
4.5.6	Nitrided surfaces.....	9
4.5.7	Pin Holes in PVD coated piston ring surface.....	10
<b>5</b>	<b>Loss of tangential force under temperature effects</b> .....	<b>10</b>
<b>6</b>	<b>Raised material caused by marking of rings</b> .....	<b>10</b>
<b>7</b>	<b>Machining of periphery and sides — Unintentional deviation from ideal profile and flatness</b> .....	<b>11</b>
7.1	General.....	11
7.2	Permissible deviations for peripheral surface profile.....	11
7.2.1	Straight faced rings according to ISO 6622 (all parts) and ISO 6624 (all parts) ..	11
7.2.2	Straight faced rings without IW/IF according to ISO 6622 (all parts), ISO 6624-1 and ISO 6624-3.....	11
7.2.3	Straight faced rings with IW/IF according to ISO 6622 (all parts), ISO 6624-1 and ISO 6624-3 and straight faced rings according to ISO 6624-2 and ISO 6624-4.....	11
7.2.4	S, G, D and DV type oil control rings according to ISO 6625.....	11
7.2.5	SF type, coil spring loaded oil control rings according to ISO 6626, ISO 6626-2, and ISO 6626-3.....	11
7.3	Permissible side face unevenness.....	11
7.4	Permissible helix.....	12
	<b>Bibliography</b> .....	<b>13</b>