ISO 14229-1:2020-02 (E)

Road vehicles - Unified diagnostic services (UDS) - Part 1: Application layer

Contents

Page

Foreword ix

Introduction x

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Symbols and abbreviated terms 5

5 Conventions 5

6 Document overview 6

7 Application layer services 7
7.1 General 7
7.2 Format description of application layer services 9
7.3 Format description of service primitives 9
7.3.1 General definition 9
7.3.2 Service request and service indication primitives 10
7.3.3 Service response and service confirm primitives 11
7.3.4 Service request-confirm and service response-confirm primitives 11
7.4 Service data unit specification 12
7.4.1 Mandatory parameters 12
7.4.2 Vehicle system requirements 14
7.4.3 Optional parameters - A_AE, application layer remote address 15

8 Application layer protocol 15
8.1 General definition 15
8.2 A_PDU, application protocol data unit 16
8.3 A_PCI, application protocol control information 16
8.4 SI, service identifier 17
8.5 A_NR_SI, Negative response service identifier 17
8.6 Negative response/confirmation service primitive 18
8.7 Server response implementation rules 18
8.7.1 General definitions 18
8.7.2 General server response behaviour 19
8.7.3 Request message with SubFunction parameter and server response behaviour 21
8.7.4 Request message without SubFunction parameter and server response behaviour 25
8.7.5 Pseudo code example of server response behaviour 27
8.7.6 Multiple concurrent request messages with physical and functional addressing 29

9 Service description conventions 29
9.1 Service description 29
9.2 Request message 30
9.2.1 Request message definition 30
9.2.2 Request message SubFunction parameter $Level (LEV_) definition 31
9.2.3 Request message data-parameter definition 33
9.3 Positive response message 33
9.3.1 Positive response message definition 33
9.3.2 Positive response message data-parameter definition 34

9.4 Supported negative response codes (NRC_) 34
9.5 Message flow examples 35

10 Diagnostic and communication management functional unit 36
10.1 Overview 36
10.2 DiagnosticSessionControl (10_{16}) service 36
10.2.1 Service description 36
10.2.2 Request message 40
10.2.3 Positive response message 41
10.2.4 Supported negative response codes (NRC_) 42
10.2.5 Message flow example(s) DiagnosticSessionControl – Start programmingSession 43
10.3 ECUReset (11_{16}) service 43
10.3.1 Service description 43
10.3.2 Request message 44
10.3.3 Positive response message 45
10.3.4 Supported negative response codes (NRC_) 46
10.3.5 Message flow example ECUReset 47
10.4 SecurityAccess (27_{16}) service 47
10.4.1 Service description 47
10.4.2 Request message 49
10.4.3 Positive response message 51
10.4.4 Supported negative response codes (NRC_) 51
10.4.5 Message flow example(s) SecurityAccess 52
10.5 CommunicationControl (28_{16}) service 54
10.5.1 Service description 54
10.5.2 Request message 54
10.5.3 Positive response message 56
10.5.4 Supported negative response codes (NRC_) 56
10.5.5 Message flow example CommunicationControl (disable transmission of network management messages) 57
10.5.6 Message flow example CommunicationControl (switch a remote network into the diagnostic-only scheduling mode where the node with address $000A_{16}$ is connected to) 57
10.5.7 Message flow example CommunicationControl (switch to application scheduling mode with enhanced address information, the node $000A_{16}$, which is connected to a sub-network, is addressed) 58
10.6 Authentication (29_{16}) service 59
10.6.1 Service overview 59
10.6.2 Authentication with PKI Certificate Exchange (APCE) 60
10.6.3 Authentication with Challenge-Response (ACR) 65
10.6.4 Common requirements 69
10.6.5 Request message 71
10.6.6 Positive response message 78
10.6.7 Supported negative response codes (NRC_) 85
10.6.8 Message flow example(s) Authentication 86
10.7 TesterPresent ($3E_{16}$) service 108
10.7.1 Service description 108
10.7.2 Request message 108
10.7.3 Positive response message 108
10.7.4 Supported negative response codes (NRC_) 109
10.7.5 Message flow example(s) TesterPresent 109
10.8 ControlDTCSetting (85_{16}) service 110
10.8.1 Service description 110
10.8.2 Request message 111

10.8.3 Positive response message ... 112
10.8.4 Supported negative response codes (NRC_) ... 112
10.8.5 Message flow example(s) ControlDTCSetting ... 113
10.9 ResponseOnEvent (86_{16}) service ... 114
10.9.1 Service description ... 114
10.9.2 Request message ... 121
10.9.3 Positive response message ... 127
10.9.4 Supported negative response codes (NRC_) ... 130
10.9.5 Message flow example(s) ResponseOnEvent ... 131
10.10 LinkControl (87_{16}) service ... 146
10.10.1 Service description ... 146
10.10.2 Request message ... 147
10.10.3 Positive response message ... 149
10.10.4 Supported negative response codes (NRC_) ... 149
10.10.5 Message flow example(s) LinkControl ... 150

11 Data transmission functional unit ... 152
11.1 Overview ... 152
11.2 ReadDataByIdentifier (22_{16}) service ... 153
11.2.1 Service description ... 153
11.2.2 Request message ... 153
11.2.3 Positive response message ... 154
11.2.4 Supported negative response codes (NRC_) ... 155
11.2.5 Message flow example ReadDataByIdentifier ... 157
11.3 ReadMemoryByAddress (23_{16}) service ... 159
11.3.1 Service description ... 159
11.3.2 Request message ... 159
11.3.3 Positive response message ... 161
11.3.4 Supported negative response codes (NRC_) ... 161
11.3.5 Message flow example ReadMemoryByAddress ... 163
11.4 ReadScalingDataByIdentifier (24_{16}) service ... 166
11.4.1 Service description ... 166
11.4.2 Request message ... 166
11.4.3 Positive response message ... 166
11.4.4 Supported negative response codes (NRC_) ... 167
11.4.5 Message flow example ReadScalingDataByIdentifier ... 169
11.5 ReadDataByPeriodicIdentifier ($2A_{16}$) service ... 172
11.5.1 Service description ... 172
11.5.2 Request message ... 176
11.5.3 Positive response message ... 176
11.5.4 Supported negative response codes (NRC_) ... 177
11.5.5 Message flow example ReadDataByPeriodicIdentifier ... 180
11.6 DynamicallyDefineDataIdentifier ($2C_{16}$) service ... 191
11.6.1 Service description ... 191
11.6.2 Request message ... 192
11.6.3 Positive response message ... 195
11.6.4 Supported negative response codes (NRC_) ... 196
11.6.5 Message flow examples DynamicallyDefineDataIdentifier ... 197
11.7 WriteDataByIdentifier ($2E_{16}$) service ... 212
11.7.1 Service description ... 212
11.7.2 Request message ... 212
11.7.3 Positive response message ... 213
11.7.4 Supported negative response codes (NRC_) ... 214
11.7.5 Message flow example WriteDataByIdentifier ... 215

11.8 WriteMemoryByAddress ($3D_{16}$) service 216
11.8.1 Service description 216
11.8.2 Request message 217
11.8.3 Positive response message 218
11.8.4 Supported negative response codes (NRC_) 219
11.8.5 Message flow example WriteMemoryByAddress 221

12 Stored data transmission functional unit 223
12.1 Overview 223
12.2 ClearDiagnosticInformation (14_{16}) service 223
12.2.1 Service description 223
12.2.2 Request message 224
12.2.3 Positive response message 225
12.2.4 Supported negative response codes (NRC_) 225
12.2.5 Message flow example ClearDiagnosticInformation 226
12.3 ReadDTCInformation (19_{16}) service 227
12.3.1 Service description 227
12.3.2 Request message 238
12.3.3 Positive response message 249
12.3.4 Supported negative response codes (NRC_) 263
12.3.5 Message flow examples – ReadDTCInformation 264

13 InputOutput control functional unit 297
13.1 Overview 297
13.2 InputOutputControlByIdentifier ($2F_{16}$) service 297
13.2.1 Service description 297
13.2.2 Request message 298
13.2.3 Positive response message 299
13.2.4 Supported negative response codes (NRC_) 300
13.2.5 Message flow example(s) InputOutputControlByIdentifier 301

14 Routine functional unit 310
14.1 Overview 310
14.2 RoutineControl (31_{16}) service 311
14.2.1 Service description 311
14.2.2 Request message 312
14.2.3 Positive response message 314
14.2.4 Supported negative response codes (NRC_) 315
14.2.5 Message flow example(s) RoutineControl 317

15 Upload download functional unit 321
15.1 Overview 321
15.2 RequestDownload (34_{16}) service 321
15.2.1 Service description 321
15.2.2 Request message 322
15.2.3 Positive response message 323
15.2.4 Supported negative response codes (NRC_) 324
15.2.5 Message flow example(s) RequestDownload 325
15.3 RequestUpload (35_{16}) service 325
15.3.1 Service description 325
15.3.2 Request message 326
15.3.3 Positive response message 327
15.3.4 Supported negative response codes (NRC_) 328
15.3.5 Message flow example(s) RequestUpload 329
15.4 TransferData (36_{16}) service 330
15.4.1 Service description 330

15.4.2 Request message ... 330
15.4.3 Positive response message ... 331
15.4.4 Supported negative response codes (NRC_) ... 332
15.4.5 Message flow example(s) TransferData ... 334
15.5 RequestTransferExit (37_{16}) service ... 334
15.5.1 Service description ... 334
15.5.2 Request message ... 335
15.5.3 Positive response message ... 335
15.5.4 Supported negative response codes (NRC_) ... 336
15.5.5 Message flow example(s) for downloading/uploading data ... 337
15.6 RequestFileTransfer (38_{16}) service ... 344
15.6.1 Service description ... 344
15.6.2 Request message ... 344
15.6.3 Positive response message ... 346
15.6.4 Supported negative response codes (NRC_) ... 348
15.6.5 Message flow example(s) RequestFileTransfer ... 350

16 Security sub-layer definition ... 353
16.1 General ... 353
16.1.1 Purpose ... 353
16.1.2 Security sub-layer description ... 353
16.1.3 Security sub-layer access ... 354
16.1.4 General server response behaviour ... 356
16.2 SecuredDataTransmission (84_{16}) service ... 358
16.2.1 Service description ... 358
16.2.2 Request message ... 358
16.2.3 Positive response message for successful internal message ... 360
16.2.4 Supported negative response codes (NRC_) ... 362
16.2.5 Message flow example SecuredDataTransmission ... 363

17 Non-volatile server memory programming process ... 366
17.1 General information ... 366
17.2 Detailed programming sequence ... 370
17.2.1 Programming phase #1 — Download of application software and/or application data ... 370
17.3 Server reprogramming requirements ... 379
17.3.1 Requirements for servers to support programming ... 379
17.3.2 Software, data identification and fingerprints ... 382
17.3.3 Server routine access ... 383
17.4 Non-volatile server memory programming message flow examples ... 383
17.4.1 General information ... 383
17.4.2 Programming phase #1 — Pre-Programming step ... 383
17.4.3 Programming phase #1 — Programming step ... 384
17.4.4 Programming phase #1 — Post-Programming step ... 389

Annex A (normative) Global parameter definitions ... 390

Annex B (normative) Diagnostic and communication management functional unit data-parameter definitions ... 400

Annex C (normative) Data transmission functional unit data-parameter definitions ... 405

Annex D (normative) Stored data transmission functional unit data-parameter definitions ... 422

Annex E (normative) Input output control functional unit data-parameter definitions ... 444

Annex F (normative) Routine functional unit data-parameter definitions ... 445

Annex G (normative) Upload and download functional unit data-parameter ... 447

Annex H (informative) Examples for addressAndLengthFormatIdentifier parameter values ... 448

Annex I (normative) Security access state chart ... 450

Annex J (informative) Recommended implementation for multiple client environments ... 458

Bibliography ... 464