

ISO 20794-2:2020-02 (E)

Road vehicles - Clock extension peripheral interface (CXPI) - Part 2: Application layer

| Contents | Page |
|---|-------------|
| Foreword..... | v |
| Introduction..... | vi |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms and definitions | 1 |
| 4 Symbols and abbreviated terms | 3 |
| 4.1 Symbols..... | 3 |
| 4.2 Abbreviated terms..... | 3 |
| 5 Conventions | 4 |
| 6 Introduction to application and application layer | 4 |
| 6.1 Application properties..... | 4 |
| 6.2 Application layer properties..... | 4 |
| 6.3 Message transmission..... | 4 |
| 6.4 Communication methods..... | 4 |
| 6.5 Message types..... | 5 |
| 6.6 Error handling..... | 5 |
| 7 Service interface parameters (SIP) | 5 |
| 7.1 SIP — General..... | 5 |
| 7.2 SIP — Data type definitions..... | 5 |
| 7.3 SIP — Mtype, message type..... | 6 |
| 7.4 SIP — ReqId, request identifier..... | 6 |
| 7.5 SIP — ReqTypeId, request type identifier..... | 6 |
| 7.6 SIP — PDU, protocol data unit..... | 6 |
| 7.7 SIP — Length, length of PDU..... | 6 |
| 7.8 SIP — ev_wakeup_ind, event wake-up indication (optional)..... | 6 |
| 7.9 SIP — cmd_wakeup_req, command wake-up request..... | 7 |
| 7.10 SIP — NMInfo, network management information..... | 7 |
| 7.11 SIP — SCT, sequence count..... | 8 |
| 7.12 SIP — Result, result..... | 8 |
| 8 SI — Service interface (SI) definition to application and lower OSI layers | 8 |
| 8.1 SI — A_Data.req and A_Data.ind service interface..... | 8 |
| 8.2 SI — A_Data.req and A_Data.ind service interface parameter mapping..... | 9 |
| 9 Application (APP) | 9 |
| 9.1 APP — Message exchange..... | 9 |
| 9.2 APP — Communication methods..... | 9 |
| 9.2.1 APP — General..... | 9 |
| 9.2.2 APP — Event-triggered method..... | 10 |
| 9.2.3 APP — Polling method..... | 10 |
| 9.3 APP — Network management (NM)..... | 11 |
| 9.3.1 APP — General..... | 11 |
| 9.3.2 APP — Normal, standby, and sleep states..... | 12 |
| 9.3.3 APP — Normal state..... | 13 |
| 9.3.4 APP — Sleep state (optional)..... | 14 |
| 9.3.5 APP — Standby state (optional)..... | 14 |
| 9.3.6 APP — Wake-up/sleep function (optional)..... | 14 |
| 9.3.7 APP — Wake-up/sleep sequence parameter..... | 24 |
| 9.4 APP — Multi clock master sequence processing..... | 24 |

| | | |
|-----------|---|-----------|
| 9.5 | APP — Measurement and/or control data | 25 |
| 9.5.1 | APP — Publisher and subscriber data | 25 |
| 9.5.2 | APP — Measurement and/or control data management | 26 |
| 9.5.3 | APP — Measurement and/or control data types | 26 |
| 9.5.4 | APP — Measurement and/or control data consistency | 26 |
| 9.5.5 | APP — Assignment of ReqId | 27 |
| 9.5.6 | APP — Priority of ReqId | 27 |
| 9.6 | APP — Error handling | 28 |
| 9.6.1 | APP — General | 28 |
| 9.6.2 | APP — CXPI network error | 28 |
| 9.6.3 | APP — Network management information | 29 |
| 9.6.4 | APP — SCT, sequence count (optional) | 30 |
| 9.6.5 | APP — Sequence count (SCT) error (optional) | 31 |
| 9.6.6 | APP — Transmission prohibition | 31 |
| 9.6.7 | APP — Retransmission | 32 |
| 9.6.8 | APP — Error notification on CXPI network (optional) | 32 |
| 10 | Application layer (AL) | 33 |
| 10.1 | AL — Message exchange | 33 |
| 10.2 | AL — Message structure | 34 |
| 10.3 | AL — Request protected type identifier field | 35 |
| 10.4 | AL — Request protected identifier field | 35 |
| 10.4.1 | AL — General | 35 |
| 10.4.2 | AL — Judgment of received message | 35 |
| 10.5 | AL — Response field (A_PDU) | 35 |
| 10.5.1 | AL — General | 35 |
| 10.5.2 | AL — A_PDU | 35 |
| 10.5.3 | AL — Wake-up indication and request | 36 |
| 10.6 | AL — Error detection | 36 |
| | Bibliography | 37 |