

# ISO 21111-4:2020-03 (E)

## Road vehicles - In-vehicle Ethernet - Part 4: General requirements and test methods of optical gigabit Ethernet components

---

| Contents  | Page |
|---|------|
| Foreword .....  | v    |
| Introduction .....                                    | vii  |
| 1 Scope .....   | 1    |
| 2 Normative references .....                          | 1    |
| 3 Terms and definitions .....                         | 2    |
| 4 Abbreviated terms .....                             | 3    |
| 5 1000BASE-RHC components .....                       | 4    |
| 6 Header connector .....                              | 5    |
| 6.1 Dimension criteria .....                          | 5    |
| 6.2 Mechanical coding .....                           | 8    |
| 6.3 Requirements of header connector .....            | 9    |
| 6.4 Evaluation .....                                  | 10   |
| 6.4.1 High storage temperature exposure .....         | 10   |
| 6.4.2 Low storage temperature exposure .....          | 10   |
| 6.4.3 Operating temperature range .....               | 11   |
| 7 Cable connector .....                               | 11   |
| 7.1 Cable plug .....                                  | 11   |
| 7.1.1 Dimension criteria .....                        | 11   |
| 7.1.2 Mechanical coding .....                         | 13   |
| 7.2 Cable socket .....                                | 13   |
| 7.2.1 Dimension criteria .....                        | 13   |
| 7.2.2 Mechanical coding .....                         | 16   |
| 7.3 Requirements of cable connector .....             | 16   |
| 7.4 Evaluation .....                                  | 16   |
| 7.4.1 High storage temperature exposure .....         | 16   |
| 7.4.2 Low storage temperature exposure .....          | 17   |
| 7.4.3 Operation temperature range (informative) ..... | 17   |
| 8 POF and POF cable .....                             | 17   |
| 8.1 POF .....   | 17   |
| 8.2 Requirements of POF .....                         | 17   |
| 8.3 Outline of POF .....                              | 18   |
| 8.3.1 Cladding diameter .....                         | 18   |
| 8.3.2 Numerical aperture .....                        | 18   |
| 8.3.3 Attenuation .....                               | 19   |
| 8.4 POF cable .....                                   | 20   |
| 8.5 Requirements of POF cable .....                   | 21   |
| 8.6 Evaluation .....                                  | 22   |
| 8.6.1 High storage temperature exposure .....         | 22   |
| 8.6.2 Low storage temperature exposure .....          | 22   |
| 8.6.3 Operation temperature range .....               | 23   |
| 8.6.4 Minimum bending radius .....                    | 23   |
| 8.6.5 Maximum bending attenuation .....               | 24   |

|        |  |    |
|--------|--|----|
| 8.6.6  | Tensile strength .....   | 25 |
| 8.6.7  | Crush .....  | 26 |
| 8.6.8  | Edge impact .....  | 27 |
| 8.6.9  | Static torsion .....   | 28 |
| 8.6.10 | Resistance to flame propagation .....                                    | 29 |
| 9      | Optical channel .....  | 30 |
| 9.1    | General .....  | 30 |
| 9.2    | Optical harness (informative) .....                                      | 30 |
| 9.3    | Positions of test points .....   | 31 |
| 9.4    | Requirements .....   | 31 |
| 9.4.1  | Electrical characteristics .....   | 31 |
| 9.4.2  | Optical characteristics .....  | 32 |
| 9.4.3  | Physical characteristics .....   | 32 |
| 9.4.4  | Temperature environmental characteristics .....                          | 33 |
| 9.4.5  | Combined environment examination .....                                   | 33 |
| 9.4.6  | Specific environmental examination .....                                 | 33 |
| 9.5    | Methodology (informative) .....  | 34 |
| 9.5.1  | Light source setup .....   | 34 |
| 9.5.2  | Excitation, test setup and measurement equipment .....                   | 34 |
| 9.5.3  | Harness setup .....  | 35 |
| 9.6    | Evaluation (characteristics of photoelectric conversion) .....           | 36 |
| 9.6.1  | Optical PMD transmitter input electrical interface .....                 | 36 |
| 9.6.2  | Optical PMD receiver output electrical interface .....                   | 38 |
| 9.7    | Evaluation (optical characteristics) .....                               | 40 |
| 9.7.1  | Minimum average output power at TP2 .....                                | 40 |
| 9.7.2  | Extinction ratio at TP2 .....  | 40 |
| 9.7.3  | EAF profile at TP2 .....   | 41 |
| 9.7.4  | Minimum average output power at TP2' .....                               | 41 |
| 9.7.5  | Minimum average output power at TP3 .....                                | 43 |
| 9.7.6  | Range of optical input power at TP3' .....                               | 43 |
| 9.7.7  | Maximum coupling attenuation at optical in-line .....                    | 45 |
| 9.8    | Evaluation (physical characteristics) .....                              | 46 |
| 9.8.1  | Minimum retention force .....  | 46 |
| 9.8.2  | Maximum insertion force .....  | 47 |
| 9.8.3  | Maximum unlock and release force .....                                   | 48 |
| 9.8.4  | Durability of repeated mating and unmating .....                         | 48 |
| 9.8.5  | Maximum cable holding force .....  | 49 |
| 9.9    | Evaluation (temperature environmental characteristics) .....             | 49 |
| 9.9.1  | High storage temperature exposure .....                                  | 49 |
| 9.9.2  | Low storage temperature exposure .....                                   | 50 |
| 9.9.3  | High operation temperature exposure .....                                | 50 |
| 9.9.4  | Low operation temperature exposure .....                                 | 51 |
| 9.10   | Evaluation (combined environmental examination) .....                    | 51 |
| 9.10.1 | General .....  | 51 |
| 9.10.2 | Flow chart of environmental load tests for optical PMD transmitter ..... | 51 |
| 9.10.3 | Operation test after durability of mate and un-mate .....                | 52 |
| 9.10.4 | Operation test after high temperature exposure .....                     | 52 |
| 9.10.5 | Operation test after temperature and vibration .....                     | 53 |
| 9.10.6 | Operation test after heat shock .....                                    | 53 |
| 9.10.7 | Operation test after humidity/temperature cycle procedure .....          | 54 |
| 9.10.8 | Operation test after specific vibration profile .....                    | 54 |
| 9.10.9 | Requirement of combined environmental examination .....                  | 54 |
| 9.11   | Evaluation (specific environmental examination) .....                    | 55 |
| 9.11.1 | General .....  | 55 |
| 9.11.2 | Individual environmental load tests for optical harness .....            | 55 |
| 9.11.3 | Operation test after specific physical impact .....                      | 55 |
| 9.11.4 | Operation test after chemical durability procedure .....                 | 55 |
| 9.11.5 | Operation test after Noxious gas exposure .....                          | 56 |
| 9.11.6 | Operation test after specific dust condition exposure .....              | 56 |
| 9.11.7 | Operation test after specific drop procedure .....                       | 56 |

|  |           |
|--|-----------|
| <b>9.11.8 Requirements of specific environmental examination .....</b> | <b>57</b> |
| <b>Annex A (informative) System power budget .....</b>                 | <b>58</b> |
| <b>Annex B (informative)Modefilter .....</b>                           | <b>60</b> |
| <b>Bibliography .....</b>  | <b>62</b> |