ISO 11452-4:2020-04 (E)

Road vehicles - Component test methods for electrical disturbances from narrowband radiated e lectromagnetic energy - Part 4: Harness excitation methods

Contents

Page

Foreword ... iv

1 Scope ... 1

2 Normative references ... 1

3 Terms and definitions ... 1

4 Test conditions ... 1

5 Test location ... 2

6 Test instrumentation ... 2
- 6.1 BCI test method ... 2
  - 6.1.1 General ... 2
  - 6.1.2 Injection probe ... 3
  - 6.1.3 Current measurement probe ... 3
  - 6.1.4 Stimulation and monitoring of the DUT ... 3
- 6.2 TWC test method ... 3
  - 6.2.1 General ... 3
  - 6.2.2 Tubular wave coupler ... 3
  - 6.2.3 50 Ω load resistor ... 4
  - 6.2.4 Stimulation and monitoring of the DUT ... 4

7 Test set-up for DUT powered by an unshielded power system ... 4
- 7.1 Ground plane ... 4
- 7.2 Power supply and AN ... 4
- 7.3 Location of the DUT ... 5
- 7.4 Location of the test harness ... 5
- 7.5 Location of the load simulator ... 5
- 7.6 Location of the harness excitation ... 6
  - 7.6.1 BCI test method ... 6
  - 7.6.2 TWC test method ... 6

8 Test setup for DUT powered by a shielded power system ... 10
- 8.1 Ground plane ... 10
- 8.2 Power supply and AN, HV-AN, AMN and AAN ... 10
- 8.3 Location of DUT ... 10
- 8.4 Location of test harness ... 11
- 8.5 Location of load simulator ... 12
- 8.6 Location of the harness excitation ... 12
  - 8.6.1 BCI test method ... 12
  - 8.6.2 TWC test method ... 13

9 Test procedure ... 26
- 9.1 General ... 26
- 9.2 Test plan ... 26
- 9.3 Test methods ... 26
  - 9.3.1 BCI test method ... 26
  - 9.3.2 Tubular wave coupler test method ... 29
- 9.4 Test report ... 30

Annex A (normative) **Calibration configuration (current injection probe calibration)** ... 32

Annex B (informative) **Test set-up transfer impedance** ... 34

Annex C (informative) **Remote/local grounding** ... 40

Annex D (informative) **Function performance status classification (FPSC)** ... 42