

ISO 15638-20:2020 (E)

Intelligent transport systems — Framework for cooperative telematics applications for regulated commercial freight vehicles (TARV) — Part 20: Weigh-in-motion monitoring

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	Conformance
6	General overview and framework requirements
6.1	General
6.2	Overview of Communication Profile C1 — Remote roadside inspection using a short-range wireless communication interrogator instigating a physical roadside inspection
6.2.1	General overview of Communication Profile C1
6.2.1.1	Communication Profile C1a— via a hand aimed or temporary roadside mounted and aimed interrogator
6.2.1.2	Communication Profile C1b — via a vehicle mounted and directed interrogator
6.2.1.3	Communication Profile C1c — via a permanent or semi-permanent roadside or overhead gantry
6.3	Overview of Communication Profile 2 — Roadside inspection using a short-range wireless communication interrogator, instigating a download of data to an application service provider
6.3.1	General overview of Communication Profile 2
6.4	Overview of Communication Profile C3 — Remote inspection addressed via an ITS-station instigating a download of data to an application service provider via a wireless communications interface (as defined in ISO 15638-2)
6.4.1	General overview of Communication Profile C3
6.5	Communications requirements
6.5.1	General communications requirements
6.5.2	Communications profile C1 requirements
6.5.3	Communications profile C2 requirements
6.5.4	Communications profile C3 requirements
7	Requirements for services using generic vehicle data
8	Application services that require data in addition to basic vehicle data
8.1	General
8.2	Quality of service requirements
8.3	Test requirements
8.4	Marking, labelling and packaging
9	Common features of regulated TARV application services
9.1	General
9.1.1	Communication Profiles C1 and C2
9.1.2	Communication Profile C3
9.2	Common role of the jurisdiction, approval authority, service provider and user
9.3	Common characteristics for instantiations of regulated application services

- 9.4 Common sequence of operations for regulated application services
 - 9.5 Quality of service
 - 9.6 Information security
 - 9.7 Data naming content and quality
 - 9.8 Software engineering quality systems
 - 9.9 Quality monitoring station
 - 9.10 Audits
 - 9.11 Data access control policy
 - 9.12 Approval of IVSs and service providers
- 10 Weigh-in-motion (WIM)
- 10.1 TARV WIM service description and scope
 - 10.1.1 Generic TARV WIM use case via the application service provider
 - 10.1.2 Types of weigh-in-motion
 - 10.1.3 WIM-O (weigh-in-motion system Onboard)
 - 10.1.4 WIM-R (weigh-in-motion system Roadway)
 - 10.1.5 Storage of the WIM data on-board the vehicle
 - 10.1.6 WIM inspection and Communication Profiles
 - 10.1.7 Specific use case of weigh-in-motion inspection by an inspector of the jurisdiction using short range equipment (Communication profiles 1 and 2)
 - 10.1.8 Description of TARV WIM regulated application service
 - 10.1.9 Description of TARV WIM application service
 - 10.2 Concept of operations for TARV WIM
 - 10.2.1 General
 - 10.2.2 Statement of the goals and objectives of the TARV WIM system
 - 10.2.3 Strategies, tactics, policies, and constraints affecting the TARV WIM system
 - 10.2.4 Organizations, activities, and interactions among participants and stakeholders of TARV WIM
 - 10.2.5 Clear statement of responsibilities and authorities delegated for TARV WIM
 - 10.2.6 Equipment required for TARV WIM
 - 10.2.6.1 TARV IVS WIM-O
 - 10.2.6.2 TARV IVS WIM-R
 - 10.2.6.3 TARV IVS WIM-O and WIM-R
 - 10.2.6.4 TARV WIM 'app'
 - 10.2.7 Operational processes for the TARV WIM system
 - 10.2.8 Role of the jurisdiction for TARV WIM
 - 10.2.9 Role of the TARV WIM prime service provider
 - 10.2.10 Role of the TARV WIM application service provider
 - 10.2.11 Role of the TARV WIM user
 - 10.2.12 Generic characteristics for all instantiations of the TARV weigh-in-motion (WIM) application service
 - 10.3 Sequence of operations for TARV WIM
 - 10.3.1 General
 - 10.4 TARV WIM service elements
 - 10.4.1 TARV WIM service element (SE) 1 — Establish 'weigh-in-motion' regulations, requirements, and approval arrangements
 - 10.4.2 TARV WIM SE2 — Request system approval
 - 10.4.3 TARV WIM SE3 — User (fleet owner) contracts with prime service provider
 - 10.4.4 TARV WIM SE4 — User (fleet owner) equips vehicle with a weigh-in-motion system
 - 10.4.5 TARV WIM SE5 — User contracts with application service provider
 - 10.4.6 TARV WIM SE6 — Application service provider uploads software into the TARV equipped vehicles of the fleet owner
 - 10.4.7 TARV WIM SE7 — Create Data
 - 10.4.8 TARV WIM SE8 — Recording of weigh-in-motion data
 - 10.4.9 TARV WIM SE10 — 'Interrogated' request for weigh-in-motion data
 - 10.4.9.1 Communication Profile 1 (via short range mobile interrogator)
 - 10.4.9.2 Communication Profile 2 (Via Short range mobile interrogator/ISO 15638-2 provision of data)
 - 10.4.9.3 Communication Profile 3 (Via ISO 15638-2 ITS-station provision of data)
 - 10.4.10 TARV WIM SE9 — Pre-programmed interval sending weigh-in-motion data to application service provider (Communication Profile 3)
 - 10.4.11 TARV WIM SE11 — End of session
 - 10.5 Generic TARV WIM data naming, content and quality
 - 10.6 WIM data content

- 10.7 TARV WIM application service specific provisions for quality of service
- 10.8 TARV WIM application service specific provisions for test requirements
- 10.9 TARV WIM application specific rules for the approval of IVSs and 'Service Providers'

Annex A (informative) WIM communication and transaction profiles

- A.1 Communication Profiles
- A.2 Communication Profile 1 — Interrogated request for weigh-in-motion data using short range 5,8 GHz DSRC communication
- A.3 Communication Profile 2 — Roadside inspection using a short-range wireless communication interrogator, instigating a download of data to an application service provider via an ITS-station
- A.4 Communication Profile 3 — Remote inspection addressed via an ITS-station instigating a download of data to an application service provider via a wireless communications interface
 - A.4.2 Obtaining weigh-in-motion data by remotely addressing the IPv6/IPv4 address of a vehicle ITS-station or its weigh-in-motion system that is wirelessly connected in accordance with one or more of the wireless media specified in ISO 15638-2.
 - A.4.3 Obtaining weigh-in-motion data by interrogating via a fixed gantry or roadside beacon is wirelessly connected in accordance with one or more of the wireless media specified in ISO 15638-2.
- A.5 Pre-programmed downloads of weigh-in-motion data (Communication Profile 3)
- A.5.1 Pre-programmed interval sending weigh-in-motion data to application service provider.
- A.6 End of session

Annex B (normative) Communication Profile for 5,8 GHz DSRC communications

- B.1 Overview and context
 - B.1.1 Overview
 - B.1.2 Use cases
 - B.1.3 Physical layer
 - B.1.4 Profile 1 transactions
 - B.1.5 Profile 1 transactions operating within EN 600 374-1, 5,8 GHz DSRC
 - B.1.6 Operating context
 - B.1.6.1 Prerequisites
 - B.1.6.2 Location constraints
 - B.1.6.3 Frames
 - B.1.6.4 Information security
 - B.1.6.5 WIM LPDU
 - B.1.6.6 Equipment design
 - B.1.6.7 Interrogator form factor
 - B.1.6.8 IVS form factor
 - B.1.6.9 Interrogator antenna form factor
 - B.1.6.10 IVS antenna form factor
 - B.1.6.11 IVS antenna position
 - B.1.7 Data retrieval protocol
 - B.1.7.1 Overview
 - B.1.7.2 Automatically repeating interrogations
 - B.1.7.3 WIM operating in a multi-service environment
 - B.1.7.4 Commands
 - B.1.7.5 Interrogation command sequence
 - B.1.8 Data structures
 - B.1.9 ASN.1 module for the WIM DSRC transaction
 - B.1.9.1 Window management
 - B.1.9.1.1 General
 - B.1.9.1.2 Example of frame exchange
 - B.1.9.1.3 State machine
 - B.1.9.1.3.1 MA-DATA.request
 - B.1.9.1.3.2 MA-DATA.indication
 - B.1.9.2 Behaviour of the IVS
 - B.1.9.3 State transitions
 - B.1.9.3.1 General
 - B.1.9.3.2 'Wait for frame'
 - B.1.9.3.3 'Validate Frame/Start Timer3 (T3)'
 - B.1.9.3.4 'Test frame type' state
 - B.1.9.3.5 'Start Timer 5 (T5)/Call the MA-DATA-ind'

- B.1.9.3.6 'Start Timer4b (T4b)
- B.1.9.3.7 Private window allocation
- B.1.9.3.8 'Start Timers4a, 5 (T4a, T5)
- B.1.9.3.9 Context marks
- B.2 5,8 GHz DSRC functions for weigh-in-motion
- B.2.1 Functions in detail
- B.2.1.1 General
- B.2.1.2 Security and encryption
- B.2.1.3 Creating and maintaining data
- B.2.1.4 Initialise communication
- B.2.1.5 Data transfer mechanism
- B.2.1.6 WIM Transaction to obtain data
- B.3 Error handling
- B.3.1 Recording of the data in the IVS
- B.3.2 Communication errors
- B.3.3 Encryption and signature errors
- B.3.4 Recording of errors
- B.3.4.1 Dynamic wireless communication
- B.3.4.2 Recommendation to use digital imaging in support of DSRC
- B.3.4.3 Failure to read
- B.4 Commissioning and periodic inspection tests for the DSRC
- B.4.1 General
- B.4.2 Tests which validate data content
- B.4.3 ECHO
- B.5 Data transfer between the IVS-DSRC and VU remote communication
- B.5.1 Physical connection and interfaces
- B.5.2 Application protocol
- B.5.3 Error handling
- B.5.3.1 Recording and communication of the Data in the IVS-DSRC
- B.5.3.2 Wireless communication errors
- B.5.3.3 Encryption and signature errors
- B.5.3.4 Recording of errors
- B.6 Commissioning and periodic inspection tests for the DSRC
- B.6.1 General
- B.6.2 ECHO

Annex C (informative) Example application data 'profiles' for 'weigh-in-motion'

- C.1 Profile 15638-20-1 — General locally specified WIM transaction
- C.1.1 Generic WIMdata transaction
- C.2 Generic TARV WIM data naming, content and quality
- C.3 Profile 15638-20-2 — DIRECTIVE (EU) 2015/719 (maximum authorized dimensions in national and international traffic and the maximum authorized weights in international traffic) Remote interrogation data concept: from on-board weigh-in-motion sensors or via in-road weigh-in-motion systems
- C.3.1 General
- C.3.2 WIM Data concept overview
- C.3.3 Payload data definition
- C.3.3.1 General
- C.3.3.2 Payload structured record
- C.3.3.3 IVS-DSRC VU payload data
- C.4 Profile 15638-20-3 — WIMRS15638Data
- C.4.1 General
- C.4.2 Payload data definition
- C.4.2.1 General
- C.4.2.2 Payload structured record
- C.4.2.3 WIM payload data (interrogation and WIM-R upload)
- C.4.2.4 Elements of Wim-O/WIM-R Data, actions performed and definitions
- C.4.2.5 Data transfer mechanism
- C.4.2.6 WIM-R data payload for transfer from roadside weigh station to IVS IVS-DSRC

Annex D (informative) End user considerations for deployment and use of 'weigh-in-motion' systems

- D.1 Weigh-in-motion systems for enforcement
- D.2 Weigh-in-motion performance standards
- D.3 Compliance with processing of personal data

- D.4 Tachograph integration with weigh in motion and data security**
- D.5 Options for expansion of service elements and WIM data content**

Page count: 106