

ISO 21111-5:2020 (E)

Road vehicles — In-vehicle Ethernet — Part 5: Optical 1-Gbit/s physical layer system requirements and test plans

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
4.1	Symbols
4.2	Abbreviated terms
5	Physical layer system requirements and interoperability test setups requirements
5.1	General
5.2	GEPOF link status requirements
5.2.1	IOP_GEPOF_REQ_LINK_STATUS_1
5.2.2	IOP_GEPOF_REQ_LINK_STATUS_2
5.3	GEPOF link-up requirements
5.3.1	IOP_GEPOF_REQ_LINK_UP_1
5.3.2	IOP_GEPOF_REQ_LINK_UP_2
5.3.3	IOP_GEPOF_REQ_LINK_UP_3
5.3.4	IOP_GEPOF_REQ_LINK_UP_4
5.3.5	IOP_GEPOF_REQ_LINK_UP_5
5.4	Channel quality requirements
5.4.1	IOP_GEPOF_REQ_CH_QLTY_1
5.4.2	IOP_GEPOF_REQ_CH_QLTY_2
5.5	Communication reliability under climatic loads requirements
5.5.1	IOP_GEPOF_REQ_RELIABILITY_TEMP_1
5.5.2	IOP_GEPOF_REQ_RELIABILITY_TEMP_2
5.5.3	IOP_GEPOF_REQ_RELIABILITY_TEMP_3
5.5.4	IOP_GEPOF_REQ_RELIABILITY_TEMP_4
5.5.5	IOP_GEPOF_REQ_RELIABILITY_TEMP_5
5.5.6	IOP_GEPOF_REQ_RELIABILITY_TEMP_6
5.5.7	IOP_GEPOF_REQ_RELIABILITY_TEMP_7
5.5.8	IOP_GEPOF_REQ_RELIABILITY_TEMP_8
5.5.9	IOP_GEPOF_REQ_RELIABILITY_TEMP_9
5.5.10	IOP_GEPOF_REQ_RELIABILITY_TEMP_10
5.6	Test set-up requirements
5.6.1	General
5.6.2	Channel requirements
5.6.2.1	Bidirectional high attenuation channel
5.6.2.1.1	Bidirectional high attenuation channel requirements
5.6.2.1.2	Example for bidirectional high attenuation channel implementation.
5.6.2.2	Bidirectional low attenuation channel
5.6.2.2.1	Bidirectional low attenuation channel requirements
5.6.2.2.2	Example for bidirectional low attenuation channel implementation
5.6.2.3	Variable attenuation channel
5.6.2.3.1	Variable attenuation channel requirements
5.6.2.3.2	Example for variable attenuation channel implementation
5.6.3	Device and LP requirements for interoperability test plan

- 6 Interoperability test plan set-ups**
 - 6.1 General**
 - 6.2 Interoperability test set-up 1**
 - 6.3 Interoperability test set-up 2**
 - 6.4 Interoperability test set-up 3**
 - 6.5 Interoperability test set-up 4**
- 7 Interoperability test plan**
 - 7.1 General**
 - 7.2 High attenuation channel with climatic load**
 - 7.3 Low attenuation channel with climatic load**
 - 7.4 Link status time**
 - 7.5 Channel quality**
- 8 Device-level physical layer conformance test set-ups requirements**
 - 8.1 General**
 - 8.2 Test set-up requirements**
 - 8.2.1 IUT requirements for device-level physical layer conformance test plan**
 - 8.2.2 GEPOF entity stress test tool requirements**
- 9 Device-level physical layer conformance test plan set-ups**
 - 9.1 General**
 - 9.2 Device-level physical layer conformance test set-up 1**
 - 9.3 Device-level physical layer conformance test set-up 2**
 - 9.4 Device-level physical layer conformance test set-up 3**
- 10 Device-level physical layer conformance test plan**
 - 10.1 General**
 - 10.2 High attenuation channel**
 - 10.3 Low attenuation channel**
 - 10.4 Optical IUT transmitter measurements**
 - 10.5 Wake-up and synchronized link sleep**
 - 10.5.1 General test cases**
 - 10.5.2 Device with multiple physical entities test cases**

Page count: 73