

ISO 22738:2020 (E)

Intelligent transport systems — Localized communications — Optical camera communication

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	IEEE 802.15.7
5.1	General requirements
5.2	OCC PHY and MAC architecture
5.3	PHY mode
5.4	Modulation schemes
5.5	MAC frame format
5.6	Dimming
5.7	Mitigation of flickering
6	ITS station
6.1	ITS station and communication architecture
6.2	ITS-S service access points
6.2.1	General
6.2.2	Communications SAPs
6.2.3	Management SAPs
6.2.4	Security SAPs
6.3	Hybrid communications support
7	Communication interface protocol stack
7.1	Communication interface parameters
7.2	Physical layer
7.3	Data link layer
7.3.1	General
7.3.2	Communication adaptation sub-layer
8	Communication interface management
8.1	General management
8.2	Management adaptation entity
8.2.1	OCC parameters and I-Parameters
8.2.2	OCC management commands and MI-SAP commands and requests
9	Procedures
9.1	Transmit procedure
9.2	Receive procedures
9.3	Management procedures
10	Conformance
11	Test methods
Annex A	(normative) Communication interface parameters

A.1	General
A.2	I-Parameters specific to ITS-OCC
A.3	Default of I-Parameters
Annex B	(normative) MI-COMMANDs
B.1	General
B.2	Required functionality
Annex C	(normative) MI-REQUESTs
C.1	General
C.2	Required functionality
Annex D	(normative) ASN.1 definitions
D.1	Overview
D.2	Module ITSocC
D.3	Definitions to be added in ISO 21218
D.4	Definitions to be added to the C-ITS Registry
Annex E	(informative) Frequency band and frequency allocation
E.1	Frequency band
E.2	Frequency allocation
Annex F	(informative) Dimming method
F.1	Overview
F.2	Dimming method
F.2.1	Dimming by controlling pulse width
F.2.2	Dimming by controlling pulse amplitude
F.2.3	Dimming by controlling brightness in out-of-band frequency

Page count: 25