

ISO 17515-2:2020 (E)

Intelligent transport systems — Evolved universal terrestrial radio access network (E-UTRAN) — Part 2: Device to device communications (D2D)

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols and abbreviated terms
5	Usage of LTE in ITS
5.1	LTE features used in ITS
5.2	Device-to-device communications (D2D)
5.3	D2D communication basics
5.3.1	General
5.3.2	User plane
5.3.3	Control plane
5.4	Service authorization
5.5	SideLink communication related identities
6	General requirements
7	ITS station
7.1	ITS station and communication architecture
7.2	Service access points
7.2.1	General
7.2.2	Communications service access points
7.2.3	Management service access points
7.2.4	Security service access points
8	Communication interface (CI) protocol stack
8.1	Physical layer
8.2	Data link layer
8.2.1	Basic behaviour
8.2.2	Data link layer communication addresses
8.2.3	Identification of higher layer protocols
8.3	Communication adaptation sub-layer
9	Communication interface (CI) management
9.1	Basic management
9.2	Management adaptation entity (MAE)
9.2.1	LTE-D2D parameters and I-Parameters
9.2.2	LTE-D2D management commands and MI-SAP commands and requests
10	Procedures
10.1	Communication interface (CI) procedures
10.1.1	Transmit procedure
10.1.2	Receive procedure
10.2	Management procedures
10.2.1	Cross-CI prioritization
10.2.2	Operational mode

10.2.3	LTE-D2D MAC address mapping
10.2.3.1	LTE-D2D SideLink communication
10.2.3.2	LTE-D2D Uu communication
10.2.3.3	LTE-D2D PC5 communication
10.2.3.4	Overview
10.2.4	CI connection procedure
10.2.5	CI state management
11	Conformance
12	Test methods
Annex A	(normative) Communication interface (CI) parameters
A.1	General
A.2	I-Parameters specific to ITS-LTE-D2D
A.3	Default values of I-Parameters
Annex B	(normative) MI-COMMANDs
B.1	General
B.2	Required functionality
Annex C	(normative) MI-REQUESTs
C.1	General
C.2	Required functionality
Annex D	(normative) ASN.1 definitions
D.1	Overview
D.2	Module ITSlted2d
D.3	Definitions to be added in ISO 21218
Annex E	(informative) CI state transitions

Page count: 26