

ISO 21780:2020 (E)

Road vehicles — Supply voltage of 48 V — Electrical requirements and tests

Contents

	Foreword
1	Scope
2	Normative references
3	Terms and definitions
4	Functional status
4.1	General
4.2	Functional status 1 (FS1)
4.3	Functional status 2 (FS2)
4.4	Functional status 3 (FS3)
4.5	Functional status 4 (FS4)
4.6	Functional status 5 (FS5)
5	Supply voltage range
6	Functional categories
7	Operating modes
8	General tests conditions
8.1	Standard tolerances
8.2	General values
8.3	Sampling rate and value resolution
8.4	Description of interfaces
8.5	Restrictions on performing the tests
8.6	Number of tested samples
8.7	Test voltages
8.8	Test procedure
8.9	Parameter check
8.10	Continuous parameter monitoring with drift analysis
8.11	Physical analysis
9	General requirements
9.1	General
9.2	Prerequisites regarding the system in which the component is applied
9.3	Component requirements
10	Tests and requirements
10.1	Test-01: nominal voltage range
10.1.1	Purpose
10.1.2	Test
10.1.3	Procedure
10.1.4	Requirement
10.2	Test-02: lower and upper transitory voltage ranges
10.2.1	Purpose
10.2.2	Test
10.2.2.1	Test case 1: lower transitory voltage range
10.2.2.2	Test case 2: upper transitory voltage range
10.2.3	Procedure
10.2.4	Requirement
10.3	Test-03: short term overvoltage

- 10.3.1 Purpose
- 10.3.2 Test
- 10.3.3 Procedure
- 10.3.4 Requirement
- 10.4 Test-04: supply component load dump control test
- 10.4.1 Purpose
- 10.4.2 Test
- 10.4.3 Procedure
- 10.4.4 Requirement
- 10.5 Test-05: starting profile
- 10.5.1 Purpose
- 10.5.2 Test
- 10.5.3 Procedure
- 10.5.4 Requirement
- 10.6 Test-06: long term overvoltage
- 10.6.1 Purpose
- 10.6.2 Test
- 10.6.3 Requirement
- 10.7 Test-07: overvoltage with consumer components which may supply electrical energy
- 10.7.1 Purpose
- 10.7.2 Test
- 10.7.2.1 General
- 10.7.2.2 Test part 1, without sink
- 10.7.2.3 Test part 2, with sink and cut-off at maximum current
- 10.7.3 Requirements for part 1 and part 2
- 10.8 Test-08: decrease and increase of supply voltage
- 10.8.1 Purpose
- 10.8.2 Test
- 10.8.3 Requirement
- 10.9 Test-09: voltage ripples
- 10.9.1 Purpose
- 10.9.2 Test
- 10.9.2.1 General
- 10.9.2.2 Reference Test
- 10.9.2.3 Voltage ripple test
- 10.9.3 Requirement
- 10.10 Test-10: reinitialisation
- 10.10.1 Purpose
- 10.10.2 Test
- 10.10.3 Requirement
- 10.11 Test-11: discontinuities in supply voltage
- 10.11.1 Purpose
- 10.11.2 Test
- 10.11.3 Requirements
- 10.12 Test-12: ground loss
- 10.12.1 Purpose
- 10.12.1.1 Scope of reference test
- 10.12.1.2 Scope of loss of GND tests
- 10.12.1.3 Test part 1: reference test to confirm communication monitoring
- 10.12.1.4 Test part 2: loss of GND48
- 10.12.1.5 Test part 3: loss of GND12/24
- 10.12.2 Requirements
- 10.12.2.1 Part 1
- 10.12.2.2 Parts 2 and 3
- 10.13 Test-13: fault current
- 10.13.1 Purpose
- 10.13.2 Test
- 10.13.3 Requirement
- 10.14 Test-14: ground offset
- 10.14.1 Purpose
- 10.14.2 Test
- 10.14.3 Requirement
- 10.15 Test-15: short circuit in signal line and load circuit
- 10.15.1 Purpose

- 10.15.2 Test
- 10.15.3 Procedure
- 10.15.4 Requirements
- 10.16 Test-16: quiescent current
- 10.16.1 Purpose
- 10.16.2 Test
- 10.16.3 Requirements

Annex A (informative) Example of functional status and functional categories

- A.1 Example of functional status
- A.2 Examples for functional categories
- A.2.1 Example A for different functional categories (FC III to FC I) of a DUT
- A.2.2 Example B for functional category FC IV

Annex B (informative) Loss of GND48 using the example CAN communication

- B.1 Rationale
- B.2 Actively sending

Page count: 44